

Construction

Dust Extractors & Air Cleaners & Accessories

Healthy Business

Dustcontrol®

www.dustcontrol.com

Dustcontrol –

Technology for Healthy Business

Removing dust from the workplace is not just a working environment and health issue, it is also a business issue. The cleaner the working environment, the better the end result. We call it **Healthy Business.**

What we offer

Dustcontrol manufactures mobile dust extractors for industrial and construction use, fixed extraction systems, peripheral equipment and accessories. We help companies all over the world to achieve a cleaner working environment. Our development department and production facilities are located in Sweden.

Using one of our solutions, you can extract dust, fumes, chips, oil spillages and other harmful substances, right at their source. The result is efficient production. A healthy working environment results in less absence due to illness, more efficient production, less downtime and better production quality.

You will find us in many different types of industries where a clean working environment is necessary. Dustcontrol supplies a complete range of products and accessories for small and large companies alike. For example, we supply advanced cleanroom solutions for the pharmaceutical and electronics industries, mobile dust extractors of various sizes for construction and rental companies and central extraction systems for the automotive and newspaper printing industries.

All of our systems are unique and tailored to each individual company's specific requirements.



Customer Focus

Dustcontrol was founded in 1972, with the idea of manufacturing extraction systems to capture dust and other pollutants at the source. We work closely with our customers, which means that we are always up to date regarding the requirements, regulations and working conditions in different types of workplace. We supply products that meet these ever-changing needs.

But it is not only products that we provide. We also provide the answers to questions such as: How can you capture and extract different kinds of particles and pollutants in the best possible way for your business? How do you deal with waste that can be recycled or reused?

All our mobile machines are equipped with a fine filter and a HEPA filter (H13) that clean the exhaust air to 99.95 %. These high-efficiency filters also have a long service life, which not only results in cleaner air, but also low filter costs.

With Dustcontrol as your business partner, you will get the answers to these and any other questions that you may have. Whatever the conditions, we develop a source extraction solution that is right for you and your business.



Service & Expertise

Our sales organisation comprises experienced technicians with specialist skills in their areas of expertise. If you need a mobile solution, we will come to your site and show you how it works. In the case of stationary installations, we can design and dimension the entire system to fully match your needs. We can take care of installation, commissioning and documentation, as well as planning a maintenance and service schedule.

We offer a complete service package, including accessories and spare parts. We manufacture and customise portable dust extractors and source extraction systems with very high levels of filtration, in which we use our proprietary filters that have set the industry standard.

As well as being responsible for delivery and installation, our project managers also train the personnel who will be working with our products and systems. In most countries, we have our own team of qualified installers with in-depth knowledge of our products.

With the help of Dustcontrol, you will achieve both a cleaner working environment and a healthy business.

Dustcontrol AB

170 employees.

Founded in 1972.

Head office and factory
in Norsborg, Sweden.

The company is family-owned.

Turnover approx. 28 million Euro.

Subsidiaries in the United Kingdom, Germany, Austria, USA and Finland.

Distributors in Europe, Asia, Australia and North & South America.

Healthy Business
Dustcontrol®

Our Symbols

1-phase

The dust extractor has a 1-phase power system.
Single motor and Twin motor.

3-phase

The dust extractor has a 3-phase power system.

ESD

The product is also available in ESD version.



Warning label – Asbestos. This device is H-classified and third party certified by a notified body according to EN 60335-2-69, Annex AA and TRGS 519.

Test Certificate – DGUV Test

We are certified according to ISO14001, ISO 9001 and ISO 45001.



All mobile Dustcontrol dust extractors are designed to comply with the requirements of EN 60335-2-69 Annex AA for H-class dust extraction, ensuring safe handling of hazardous dusts.

Dustcontrol AB makes every effort to maintain the accuracy and quality of the information provided in this catalogue. However, Dustcontrol AB cannot guarantee and assumes no legal liability or responsibility for the accuracy or completeness of the information provided. The information contained in this catalogue is for general guidance only.

The copyright of all content on this catalogue is owned by Dustcontrol AB. No part of the Dustcontrol AB catalogue may be changed, reproduced, stored in or transmitted on any website or medium without the prior written permission of Dustcontrol AB. Requests to republish any material must be sent to support@dustcontrol.se In case of any questions or remarks, feel free to contact us.

Published by Dustcontrol AB 2026 © www.dustcontrol.com. Prod No 903012.

Index

Machines for every Job 6-7
Choose the right machine 8-9
What do the letters mean against our products? 12

1-phase **Dust Extractors – Single motor**
- DC 1800 & DC 1800 XL 13
- DC 2900 a/c/Longopac 14-15
- DC 1800 Asbestos 16
- DC 2900 Asbestos 17
- DC Tromb H 400 20
- DC Tromb H Twin 21
- DC Tromb 600 Longopac 22
- DC Tromb 400 Asbestos 23
- DC Chip Extractor 24

3-phase **Dust Extractors – Three phase**
- DC Tromb Turbo 29
- DC Storm 500/600/700 30-33
- DC 5900 9.2 kW S/P 34
- DC 5900 Asbestos 35
- DC Turbo Tromb Asbestos 35

Compare our Dust Extractors 38-39
- Semi-Mobile Systems 40-41
- Dustcontrol Wet-Vacs 42-43

Dustcontrol Air Cleaners
- DC AirCube 600 46
- DC AirCube 1200/2000 47

Decontamination Systems
- DC Decontamination Box 50-51

Dustcontrol Pre-Separators
- DCF Tromb & DCF Storm 54
- DCF 60 & DCF 2900 55
- DCF Cyclone Separator Cover 55
- DCF Wheelbarrow 56
- DCF Tipping Container 56

Classification of Dust Extractors & HEPA Filters 58-59

Accessories and Hoses
- Cleaning Accessories 61-67
- Suction Casings 70-77
- Dustlight 78-79
- Dust Protection Door 80-81
- Plastic Bags 82-83
- Choose the Right Filter 84-85
- Filters 86-89

Premium Packaging 90
Worldwide Distributors 93
Strategy & Certification 94
Check out our QR-codes 95
Dustcontrol Service 96

Machines for every job



No matter who you are and what type of work you are involved in, we have exactly the right machines for you and the job that you do. Small and agile or big and powerful? Only you know which Dustcontrol machine is the right one for you.


Construction Worker
Carpenter
Painter

Choose the Right Machine

1-phase Single motor Dust extractor

DC 1800. The DC 1800 and DC 1800XL are high-quality, compact versions of our best-selling DC 2900. It combines ease of use with a large suction capacity and high level of filtration.

DC 2900. A small, lightweight dust extractor that can handle tough conditions. Equipped with a cyclone inlet, reverse pulse filter cleaning and separate HEPA filter.

Task or tool

Drilling
Cleaning Ø38 mm/1.5”
Reciprocating saw
Jig saw
Abrasive disc Ø125 mm/5”
Fibre disc Ø125 mm/5”
Small crosscut and mitre saw, jackhammer
Personal decontamination
Depressed centre disc Ø125 mm/5”
Wall sander Ø125 mm/5”
Oscillating machine

1-phase Twin motor Dust extractor

DC Tromb 400, is a compact, powerful, robust and efficient 1-phase dustextractor. There are three versions within the Tromb family: DC Tromb H 400 dust extractor, DCF Tromb pre-separator and a DC Tromb H 400 Twin dust extractor and pre-separator in one.

DC Tromb 600 is our latest powerful single-phase dust extractor. Launched for the North American market only.

Task or tool

Abrasive disc Ø230 mm/9”
Grooving saw 2xØ150 mm/6”
Jackhammer, Circular saw
Concrete floor grinding max 500 mm/19”
Max 800 mm/32”
Depressed centr. disc Ø230 mm/9”
Concrete milling machine
Chipping hammer
Cleaning Ø50 mm/2”
Filler sanding

3-phase Dust extractor

DC Storm 500, 600 and 700
DC Storm is compact, simple to transport and powerful. All these models feature a direct-driven, three-phase turbo pump suitable for continuous operation, heavy material transport, source extraction and cleaning. Equipped with frequency converters are suitable for use when only 16A access is available.

DC Tromb Turbo (Direct start or VFD), are equipped with a powerful three-phase turbo motor which is suitable for heavy cleaning (38 mm/1.5” accessories).

Task or tool

Concrete floor grinding 850 mm/33,5”
Abrasive disc Ø300 mm/12”
Suction lance Ø76 mm/3”
Concrete milling machine
Depressed centre disc Ø300 mm/12”
Semi-mobile system
Material transport
Brick saw Ø400 mm/16”
Cleaning Ø50 mm/2”

Wet-vac

DC 50W and DC 75W. Sucks up water and slurry in all situations, for example when making holes with a diamond saw. The slurry can be collected in a filter bag. The unit is equipped with a submersible pump for continuous evacuation of the water.

Task or tool

Drilling
Demolition
Water damage



DC 50W DC 75W

Air cleaner

DC AirCube 600, 1200 and 2000
Air cleaners are used as a complement to source extraction in very dusty environments. Recommended air change is 10 times per hour minimum.

Task or tool

Jackhammering, wall sanding, concrete grinding, demolition work, kitchen and bathroom renovation, and other construction work

Pre-separators
When large quantities of dust are produced, we recommend a pre-separator:


DCF 2800


DCF 60


DC 1800


DC 1800 XL


DC 2900L


DCF Tromb


DC Tromb H 400a


DC Tromb H Twin 400cL


DC Tromb H 600L


DCF Storm


DCF Wheelbarrow


DC Tromb Turbo


DC Storm 600L


DC AirCube 600


DC AirCube 1200


DC AirCube 2000





1-Phase Dust Extractors



What do the letters mean against our products?

These letters describe which collection container comes with our machines. For our twin-models we use a combination, CL, AA and CA.

We also use abbreviations for the various performance, usage and material of the machines. We hope this will make your selection easier and quicker.

Collection Containers:

C Bag
A Container
L Longopac bag

Performance, Usage and Material:

DC Dust Extractor / Air Cleaner
DCF Pre-Separator
EX ATEX-Compliant
FC Food Contact / Pharma Contact
H This device is H-classified and third party certified by a notified body according to EN 60335-2-69 Annex AA.
I Industry-Line
P Turbo pump in Parallel drive
S Turbo pump in Serial drive
SS Stainless Steel container/cyclone
TR Compressed air driven
Turbo Turbo-3-phase motor

Single-Phase Dust Extractors

DC 1800 H


This machine is particularly suitable for general cleaning and source extraction from handheld power tools (with suction casings up to Ø125 mm/5”) and small table saws.

The DC 1800 H is equipped with a container. A plastic bag can be used inside the container to facilitate the emptying of dust and other material.

Part No DC 1800 H

101800	230V /50Hz, EU
101801	230V /50Hz Auto start*, EU
101808	230V /50Hz, CH
101810	115V /50Hz, UK
101820	230V /50Hz, UK
101830	115V /60Hz, US/CAN
101809	230V /50Hz, AU

1-phase



Supplied with (Part No)

Suction hose (Ø38 mm/1.5”), 5 m (2111)
Suction hose, antistatic (Ø38 mm/1.5”), 5 m/16 ft (2012)
UK/US/CAN models
Connecting sleeve (2115)
Coupling socket (2108)
Floor nozzle (B370 mm/W17”) (7235)
Suction pipe (Ø38 mm/1.5”) (7257)
Plastic bag (42291)
Bag support frame (42369)
Fine filter, cellulose (42029)
HEPA H13 filter (42027)

Optional HEPA filter:
HEPA H14 filter (42926)

Technical data

HxWxD [mm/in]	780x405x390/31x16x15
Weight [kg/lb]	14/31
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [l/gal]	20/5.2
Flow max, fan, EU [m^3/h]	205
Flow max, fan, UK 115V/230V [m^3/h]	190/205
Flow max, fan, US/CAN 115V [cfm]	126.5
Negative pressure, max, EU/UK [kPa]	24
Negative pressure, max, US/CAN [inwg]	84
Power 115/230V [W]	1340/1285
Sound level [dB(A)]	68

DC 1800 XL

The DC 1800 XL is especially suited for parquet grinding and other working operations that produce light dust. Suitable for general cleaning and source extraction from handheld power tools (with up to 5” suction casings) and small table saws. It is slim, lightweight and ideal for those that need a highly portable machine that is powerful enough for source extraction. Equipped with a steel container.

Part No DC 1800 XL

101880	230V /50Hz, EU
101881	230V /50Hz, Auto start*, EU
101884	230V /50Hz, UK
101885	115V /60Hz, USA
101887	115V /60Hz, CAN
101888	230V /50Hz, CH

1-phase



Supplied with (Part No)

Suction hose antistatic (Ø38 mm 1.5”) 5 m (2012+2114)
Coupling socket 50/38 (2108)
Fine filter, cellulose (42029)
HEPA H13 filter (42027)
Pastic bag (42285)

Optional HEPA filter:
HEPA H14 filter (42926)

Technical data

HxWxD [mm/in]	1160x380x380/46x15x15
Weight [kg/lb]	19/42
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [l/gal]	55/14.5
Flow max, fan, EU [m^3/h]	205
Flow max, fan, UK 115V/230V [m^3/h]	190/205
Flow max, fan, US/CAN 115V [cfm]	126.5
Negative pressure, max, EU/UK [kPa]	24
Negative pressure, max, US/CAN [inwg]	84
Power 115/230V [W]	1340/1285
Sound level [dB(A)]	68

*) DC 1800 Auto start. Plug the handheld power tool into the power socket on the unit. Set the selector switch to the AUTO position. The dust extractor will start automatically when the power tool is started. Power connected tool – min 200 W.

Single-Phase Dust Extractors

With **plastic bag**

DC 2900

The DC 2900c is our most popular dust extractor. It is suitable for vacuum cleaning and source extraction from handheld power tools (with suction casings up to Ø125 mm/5") and small table saws. The DC 2900c has a sturdy steel chassis with large wheels, but is still light and portable.



Part No DC 2900c

120000	230V /50Hz, EU
120003	230V /50Hz, UK
120008	230V /50Hz, CH
120013	115V /50Hz, UK
120015	115V /60Hz, US/CAN
120100	230V /50Hz, Auto start*, EU
120103	230V /50Hz, Auto start*, UK
120009	230V /50Hz, AU

1-phase

Supplied with (Part No)

Suction hose (Ø38 mm/1.5"), 5 m/16 ft (2111)
Suction hose, antistatic (Ø38 mm/1.5"), 5 m/16 ft (2012) UK/US/CAN models
Connecting sleeve (2115)
Coupling socket (2108)
Floor nozzle B370/W17" (7235)
Suction pipe Ø38 mm/1.5" (7257)
Plastic bag (42702)
Fine filter, cellulose (42029)
HEPA H13 filter (42027)

Optional HEPA filter:
HEPA H14 filter (42926)


Technical data

HxWxD [mm/in]	1110x445x570/44x17x22
Weight [kg/lb]	16/35
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [l/gal]	30/7.9
Flow max, fan, EU [m³/h]	205
Flow max, fan, UK 115V/230V [m³/h]	190/205
Flow max, fan, US/CAN 115V [cfm]	126.5
Negative pressure, max, EU/UK [kPa]	24
Negative pressure, max, US/CAN [inwg]	96
Power 115/230V [W]	1284/1285
Sound level [dB(A)]	68

With **container**

DC 2900 H

Collection in a container makes the DC 2900a H ideal to use for sharp material such as metal chips.



Part No DC 2900a H

121000	230V /50Hz, EU
121003	230V /50Hz, UK
121008	230V /50Hz, CH
121013	115V /50Hz, UK
121015	115V /60Hz, US/CAN
121100	230V /50Hz, Auto start*, EU

1-phase

*) DC 2900 Auto start. Plug the handheld power tool into the power socket on the unit. Set the selector switch to the AUTO position. The dust extractor will start automatically when the power tool is started. Power connected tool – min 200 W.

Supplied with (Part No)

Suction hose, antistatic (Ø38 mm/1.5"), 5 m/16 ft, (2012)
Floor nozzle B370 /W17" (7235)
Suction pipe Ø38 mm/1.5" (7257)
Fine filter, polyester (42028)
HEPA H13 filter (42027)

Optional HEPA filter:
HEPA H14 filter (42926)

Technical data

HxWxD [mm/in]	1145x445x630/45x17x25
Weight [kg/lb]	22/48
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [l/gal]	40/10.6
Flow max, fan, EU [m³/h]	205
Flow max, fan, UK 115V/230V [m³/h]	190/205
Flow max, fan, US/CAN 115V [cfm]	126.5
Negative pressure, max, EU/UK [kPa]	24
Negative pressure, max, US/CAN [inwg]	96
Power 115/230V [W]	1285/1285
Sound level [dB(A)]	68

With **Longopac**

DC 2900

The DC 2900 is our most popular dust extractor. It is suitable for vacuum cleaning and source extraction from handheld power tools (with suction casings up to Ø125 mm/5”) and small table saws.

We are now launching DC 2900L with Longopac output, a flexible bag system, where dust is collected in a closed system.The DC 2900L can be ordered with a plastic bag/Longopac (DC 2900c/DC 2900L) or a container (DC 2900a).

Part No DC 2900L

122000	230V, EU
122003	230V, UK
122008	230V, CH
122013	115V, UK
122015	115V, UL
122100	230V, Auto start*, EU
122108	230V, Auto start*, EU
122009	230V, AU

Supplied with (Part No)

Suction hose (Ø38 mm/1.5”), 5 m/16 ft (2111)
Suction hose, antistatic (Ø38 mm/1.5”), 5 m/16 ft (2012) UK/US/CAN models
Connecting sleeve (2114)
Coupling socket (2108)
Floor nozzle B370/W17” (7235)
Suction pipe Ø38 mm/1.5” (7257)
Longopac Mini (44763)
Fine filter, cellulose (42029)
HEPA H13 filter (42027)

Optional HEPA filter:
HEPA H14 filter (42926)

Accessories (Part No)

Longopac Mini (10 pcs á 8 m) (44763)
Longopac Mini (4 pcs á 23 m) (432177)

1-phase

*) DC 2900 Auto start. Plug the handheld power tool into the power socket on the unit. Set the selector switch to the AUTO position. The dust extractor will start automatically when the power tool is started. Power connected tool – min 200 W.

Technical data

HxWxD [mm/in]	1110x445x570/44x17x22
Weight [kg/lb]	19/42
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [m/ft]	Longopac
Flow max, fan, EU [m^3/h]	205
Flow max, fan, UK 115V/230V [m^3/h]	190/205
Flow max, fan, US/CAN 115V [cfm]	126.5
Negative pressure, max, EU/UK [kPa]	24
Negative pressure, max, US/CAN [inwg]	96
Power 115V/230V [W]	1340/1285
Sound level [dB(A)]	68





DC 1800 H Asbestos

The DC 1800 H Asbestos complies with the most stringent requirements and is IFA* certified. Asbestos is a known cancer causing material that should be removed with caution. This dust extractor is equipped with an antistatic hose, a plug for the cyclone inlet, plastic bags and other safety features.

Don't take risks with your health when removing asbestos!

Supplied with (Part No)

Suction hose antistatic (Ø38 mm /1.5"), 5 m /16 ft (2012)
Coupling socket (2108)
Floor nozzle B370 mm /W17" (7235)
Suction pipe Ø38 mm /1.5" (7257)
10 x plastic bags (42285)
Bag support frame (42369)
Motor cooling filter (432183)
Fine filter, polyester (42028)
HEPA H13 filter (42027)
Inlet plug (42250)

Part No DC 1800H Asbestos

101800-1	230V, EU
101808-1	230V, CH
101810-1	115V, UK



*Institute for occupational safety and health of the German Social Accident Insurance.

Technical data

HxWxD [mm/in]	740x380x380/429x15x15
Weight [kg/lb]	14/31
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [l/gal]	20/5.3
Flow max, fan, EU [m³/h] Flow max, fan, UK 115V/230V [m³/h] Flow max, fan, US/CAN 115V [cfm]	205 205 126.5
Negative pressure, max, EU/UK [kPa] Negative pressure, max, US/CAN [inwg]	21/24 84/96
Power 115/230V [W]	1340/1285
Sound level [dB(A)]	68





DC 2900 H Asbestos

Asbestos is a known cancer causing material that should be removed with caution. This dust extractor is equipped with an antistatic hose, a plug for the cyclone inlet, plastic bags and other safety features.

Our asbestos machine DC 2900 H Asbestos comes in three versions: (A steel container), Intellibag (C) and Longopac (L) as discharge arrangements.

The DC 2900 H C/L Asbestos variants are fitted with a protective enclosure for the safe handling of asbestos waste. This protects the plastic discharge bag or Longopac liner. The handling of the protective enclosure is described in the manual for the machine.This model is certified in Institute for occupational safety and health of the German Social Accident Insurance.

Supplied with (Part No)

Suction Hose 38 Antistatic 5m (2012) + Connecting Sleeve Ø38/38 Turnable (2114) (=201201)
Coupling Socket Ø50/38 (2108)
HEPA Filter DC 1800/2900 (42027)
Fine Filter Polyester DC (42028)
Floor Nozzle 370 A-38 (7235)
Suction Pipe Ø38 Steel (2 pcs) (7257)
Plastic Bag (42285)
Intellibag (42702)
Longopac Mini (44763)

Part No DC 2900H Asbestos

125000 A/Container, EU
125100 C/Bag, EU
125200 L/Longopac, EU

The machines are tested and certified according to:
IEC 60335-1
IEC 60335-2-69, 22.Annex AA.
TRGS 519



Technical data

HxWxD [mm/in]	1110x440x550/43x17x21
Weight [kg/lb]	22/48.5 16/35.3 19/42
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [l/gal]	40/10.6 30/7.9 Longopac
Flow max, fan, EU [m³/h] Flow max, fan, UK 115V/230V [m³/h] Flow max, fan, US/CAN 115V [cfm]	205 205 126.5
Negative pressure, max, EU/UK [kPa] Negative pressure, max, US/CAN [inwg]	21/24 84/96
Power 115/230V [W]	1340/1285
Sound level [dB(A)]	70







1-Phase Dust Extractors

DC Tromb H 400



Dustcontrol has taken the DC Tromb H 400 to a new level. There are now three new versions within the Tromb family: DC Tromb H 400 dust extractor, DCF Tromb pre-separator and a DC Tromb Twin dust extractor and pre-separator in one.

As always, we are focusing to meet modern safety requirements along with an ergonomic and modular function. One of the major updates is that the new DC Tromb Twin model is separable. The dust extractor and pre-separator are easily detached and re-assembled from each other making transport simple.

Other important updates include a simpler filter change system and a motor package that is easier to remove. As well as that, improved motors and a sturdier chassis mean that the whole range has gone through a major expansion and upgrade.

Part No	DC Tromb H 400
171500	c 230V 3000W, EU
171501	c 115V, UK
171502	c 115V, US
171503	c 2600W 230, UK
171507	c 115V, CAN
171508	c 230V 3000W, CH
171530	L 230V 3000W, EU
171531	L 115V, UK
171532	L 115V, US
171533	L 230V 2600W, UK
171537	L 115V, CAN
171538	L 230V 3000W, CH
172000	a 230V 3000W, EU
172001	a 115V, UK
172002	a 115V US
172003	a 230V /2600W, UK
172008	a 230V /3000W, CH
172500	cc 230V /3000W, EU
172507	cc TWIN 115V, CAN
172530	cL TWIN 230V /3000W, EU
172531	cL TWIN 115V, UK
172532	cL TWIN 115V, US
172537	cL TWIN 115V, CAN
172538	cL TWIN 230V /3000W, CH
172540	aL TWIN 230V /3000W, EU
172520	aa TWIN 230V /3000W, EU
172523	aa TWIN 230V /2600W, UK
172528	aa TWIN 230V /3000W, CH
172550	LL TWIN 230V /3000W, EU
172552	LL TWIN 115V, US
172557	LL TWIN 115V, CAN
172539	cL TWIN 230V /3000W, AU
171539-1	L 230V 2600W, AU
171539	L 230V 3000W, AU
171539-2	L 230V 3000W, AU
171506	c 230V 3000W, NL
171536	L 230V 3000W, NL
172006	a 230V 3000W, NL

1-phase

Supplied with (Part No)

Connecting sleeve (2129)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 5 m/16 ft (2013)
Suction hose (Ø50 mm /2") 5 m /16 ft (2401) for model 171500 and 171508
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Fine filter, polyester (44017)
HEPA H13 filter (44016)

Discharge

a) 40 l /10.6 US gal container (40070) and 5 x plastic bags (42285)
c) 10 x plastic bags (43619)
L) Longopac 23 m /75 ft (432177)



Technical data

HxWxD [mm/in]	1415x600x780/56x23x31
Weight [kg/lb]	a) 51/112 c) 46/101.4 L) 50/110.2
Inlet Ø [mm/in]	76/3
Collection container [l/gal]	a) 40/10.6 c) 33/8.7 L) Longopac
Flow max, fan, EU [m^3/h] Flow max, fan, UK 115V/230V [m^3/h] Flow max, fan, US/CAN 115V [cfm]	420 360/420 212
Negative pressure, max, EU/UK [kPa] Negative pressure, max, US/CAN [inwg]	21 (+/- 10%) 84
Power 115/230V [W]	2100/2680/3000
Sound level [dB(A)]	70







DC Tromb H Twin

SERVICE KITS

Service Kit for DC Tromb Twin

With a DCF Tromb Kit you can connect the dust extractor DC Tromb Twin with the pre-separator DCF Tromb.

DCF Tromb Kit L (707010)
DCF Tromb Kit c (707011)
DCF Tromb Kit a (707012)

Service Kit for DC Tromb 400

With a DC Tromb Service Kit you have everything you need for meintenance; filters and part for the brusch mechanism.

Service Kit Part no 45525 consists of:

HEPA H13 filter (44016)
Fine filter, polyester (44017)
Motor Brush mechanism (44707):
(44308 + 43306-1)

Supplied with (Part No)

Antistatic hose set (Ø50 mm /2") mm x 7,5 m/25 ft
(Part No 2013+2129+2008)
Floor nozzle (B500 mm /W 19.7") (7238)
Suction pipe (Ø50 mm /2") (7265)
a-model (AA, AL) 5 x plastic bags (42285)
c-model (CC) with 10 x plastic bags (43619)
L-model (CL) with Longopac 25 m (432177)
+ 10 x plastic bags (43619)
Fine filter, polyester (44017)
HEPA H13 filter (44016)

Technical data

HxWxD [mm/in]	1415x600x1280/56x23x50
Weight [kg/lb]	CC) 71/168 CL) 80/173
Inlet Ø [mm/in]	76/3
Collection container [l/gal]	C) 33/8.7 L) Longopac
Flow max, fan, EU [m³/h] Flow max, fan, UK 115V/230V [m³/h] Flow max, fan, US/CAN 115V [cfm]	420 360/420 212
Negative pressure, max, EU/UK [kPa] Negative pressure, max, US/CAN [inwg]	21 (+/- 10%) 84
Power 115/230V [W]	2100/2680/3000
Sound level [dB(A)]	70

DC Tromb 600 L





Supplied with (Part No)

Connecting sleeve (2129)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 5 m/16 ft (2013)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Fine filter, polyester (44017-1)
HEPA H13 filter (44016-1)

Technical Data

HxWxD [mm/in]	1600x600x800/63x24x31
Weight [kg/lb]	63/143
Collection container [l/gal]	L) Longopac
Flow max, fan, EU/US [m³/h/cfm]	600/353
Negative pressure, max, EU/US [kPa/inwg]	21 (+/- 10%) / 84
Power 230V/50Hz/60Hz [W]	4050

Part No DC Tromb 600 L 181532 230V /60Hz, US

1-phase



Protected shutter valve



Locking ring for pre-filter

Microfilter/ HEPA H13 filter

The DC Tromb 600 is our most powerful single-phase dust extractor. It is designed to meet modern safety requirements and to work in conjunction with tools that have become ever more efficient and therefore produce more dust than they have previously. The maximum airflow is as high as 600 m³/h = 353 cfm, which is more than enough capacity for equipment such as large floor grinders and large electric cut-off saws.

Not only is the DC Tromb 600 compact, powerful and efficient, but it's versatile too. It is easy to transport around construction sites, move in stair-wells and lift into tight spaces. The wheels are puncture-proof and won't leave marks on the floor. The front wheels are lockable for working on uneven ground. The DC Tromb 600 is adapted for all types of fine dust such as concrete (silica), plaster, wood and filler dust.

The machine comes equipped as standard with a fine filter (rinsable polyester) and an HEPA H13 filter that complies with OSHA regulations. A filter monitor shows the user when it's time to clean the filter. Filter cleaning can be done automatically during operation, or once the work has been completed.



DC Tromb 400 H Asbestos

Supplied with (Part No)

Connecting sleeve (2129)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 5 m/16 ft (2013)
Floor nozzle B500 mm /W19,7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Air filter (44034)
Fine filter, polyester (44017)
HEPA H13 filter (44016)
5 x plastic bags (42285)
Plastic bags,10 pcs, 20 l (43619) (C)
Longopac Mini Superstrong, 4x23 m (432177) (L)


Technical data DC Tromb 400 H Asbestos A/C/L

HxWxD [mm/in]	1415x560x700/56x22x27
Weight [kg/lb]	50/110
Hose length Ø38 mm /1.5" [m/ft]	5/16
Collection container [m/ft]	40/10.6
Flow max, fan, EU [m³/h]	393
Flow max, fan, UK 115V/230V [m³/h]	393
Flow max, fan, US/CAN 115V [cfm]	231
Negative pressure, max, EU/UK [kPa]	21/24
Negative pressure, max, US/CAN [inwg]	84/96
Power 115V/230V [W]	3000
Sound level [dB(A)]	70

Part No DC Tromb 400 H Asbestos

175000	a 230V 3000W, EU
175003	a 230V 2600W, UK
175008	a 230V 3000W, CH
175100	c 230V 3000W, EU
175200	L 230V 3000W, EU
175000	a 230V 3000W, EU

1-phase





DC Tromb 400 H Asbestos A



DC Tromb 400 H Asbestos C

The DC Tromb 400 H Asbestos is our most powerful 1-phase dust extractor up to now. It is designed to cope with both the demands for a clean and healthy working environment and handheld power tools which are more effective than ever. The dust extractor also enables the user to work without unneccessary interruptions – it tackles up to 400 m³/h. The dust extractor has been DGUV tested and approved by IFA (Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung).

The DC Tromb is not just powerful, robust and effective but also versatile and all-round. It can handle all kinds of fine dusts and materials created on a construction site created from cutting concrete, sanding, grinding or drilling floors or walls as well as dust from many other industrial factory processes. The machine can be connected to floor grinders and handheld tools like cutting machines, chisel hammers and saws. Due to its compact design the DC Tromb is also easy to move and transport.

As a standard the machine is equipped with a patented self-cleaning filter (washable polyester) and a H13-filter built to be Application Class H. A signal lamp shows when it's time to clean the filter.*

Accessory

44076 Merged outlet

The DC Tromb 400 H Asbest can be equipped with a new sound absorber, which has one outlet Ø76 mm instead of two. The sound absorber is made of stainless steel. The new outlet will make it easy for the customer to evacuate odour and to minimize air flow in the room.

* Switch operated reverse pulse filter cleaning

Single-Phase Dust Extractors

DC Chip Extractor

The new DC Chip Extractor replaces the previous model DC 3800 Wood Shavings Extractor.

This new machine is based on the DC Tromb chassis and DC Tromb engine package. It is equipped with multiway socket, 3-phase, has updated tighter container and a higher air flow and also larger filter area.

This machine is suitable for general cleaning and source extraction on most saws where continuous operation and a high separation rate are required. It is robust, mobile device that is easy to move. Can be used either as a standard 230 V machine or, as a part of a system with 3-phase cord, with auto start connected to a saw machine



Part No DC Chip Extractor

174100 230V /50Hz, EU

Supplied with (Part No)

Connecting sleeve (2107)
Coupling socket (2129)
Suction hose Ø50 mm/2", 7.5 m/ 22 ft antistatic (2013)
Plastic bag, 90 l, 1pc (4714)
Fine filter, polyester (44017)
HEPA H13 filter (44016)


Technical data

HxWxD [mm/in]	1530x600x780/60x23.5x31
Weight [kg/lb]	69/152
Hose length Ø50 mm [m/ft]	7.5/25
Collection container [l/gal]	100/26
Flow max, fan, EU [m³/h/CFM]	355/209
Negative pressure, max, EU [kPa/inwg]	22/88
Power 115/230V [W/Hp]	2600/3.5
Sound level [dB(A)]	70

1-phase




Dustc
TRON



Capture dust with source extraction.

All dust on construction sites is a health hazard in the long term. However, there are some types of dust that are hazardous in the short term too. It has become standard practice for modern construction companies to take the health of their employees seriously and to minimise the levels of dust in the workplace.

Source extraction means that the dust is captured before it spreads and before it can be breathed in. Dust levels can be significantly reduced by fitting all power tools with suction casings and connecting these to efficient dust extractors.

Cleaning should be carried out with a dust extractor with the classification H. The dust extractor should be equipped with a HEPA filter to prevent the spread of the finest dust particles. Sweeping simply stirs the hazardous dust up into the air, subjecting those in the area to further exposure. To put it simply, source extraction and cleaning using approved dust extractors are absolutely vital.



3-Phase Dust Extractors

Quality, Containment & Performance – All in one.



TROMB

DC Tromb Turbo

DC **Tromb** Turbo Twin

The DC Tromb Turbo Twin is the successor to the DC 3900 Turbo Twin and, like this, a very powerful dust extractor. It is particularly suitable for concrete grinding since 80–90% of the coarse materials are separated in the pre-separator.The remaining dust goes into the filter cyclone.



3-phase

Part No	DC Tromb Turbo Twin
173320	aa 2.2kW, EU
173340	LL 2.2kW, EU

Technical data

HxWxD [mm/in]	1415x600x 380/56x24x54
Weight [kg/lb]	a) Container 112/247 L) Longopac 112/247
Collection container [l/gal]	a) 40/10.6 L) Longopac
Flow max, fan, EU [m³/h]	249
Negative pressure, max, EU [kPa]	29
Power [kW]	2.2
Sound level [dB(A)]	72

Three-Phase Dust Extractors

With **direct start**

DC **Tromb** Turbo

The DC Tromb Turbo is a medium sized dust extractor that expands the Tromb family. It is equipped with a powerful three-phase turbo motor which is suitable for heavy cleaning (38 mm/1.5" accessories) and is delivered with 7 m hose. Suitable for source extraction from medium sized power tools such as grinders, jack hammers and saws. Thanks to the tall cyclone, large filters and powerful motor package, it can handle large amounts of debris.



Part No — DC Tromb Turbo a/c/L

173500	a 2.2kW, EU
173100	c 2.2kW, EU
173300	L 2.2kW, EU
173502	a 4hp 460V /60Hz, US
173102	c 4hp 460V /60Hz, US
173302	L 4hp 460V /60Hz, US
173107	c 4hp 600V /60Hz, CAN

3-phase

Supplied with (Part No)

Suction hose set, 7 m /23 ft, 5 m /16 ft (Ø50 mm /2”) and 2 m /6.5 ft (Ø38 mm /1.5”), (2126)
Floor nozzle B450 mm (7236)
Suction pipe (Ø38 mm /1.5”) (7257)
Connecting sleeve (2114)
Coupling socket (2107)
Fine filter, polyester (44017)
HEPA H13-filter (44016)
a-model 5 x plastic bags (42285)

Technical data

HxWxD [mm/in]	1415x600x840/56x23x33
Weight [kg/lb]	a) Container 88/194 c) Bag 84/185 L) Longopac 86/190
Collection container [l/gal]	a) 40/10.6 c) 20/5.3 L) Longopac
Flow max, fan, EU [m³/h] Flow max, fan, US/CAN [cfm]	260 186
Negative pressure, max, EU [kPa]	28
Power [kW]	2.2
Sound level [dB(A)]	72

With **frequence inverter (VFD)**

DC **Tromb** Turbo

DC Tromb Turbo is also available with a frequence inverter (VFD) and we would like to introduce the Longopac version. This model gives approx. 50% more filter area on the HEPA filter than its predecessor (5% more filter area for the fine filter). New safety features such as overheating protection is added. With the semi automatic filter cleaning and quick coupling for filter change, this machine gets the job done.



Part No — DC Tromb Turbo VFD a/c/L

173400	a 2.2kW, EU
173000	c 2.2kW, EU
173200	L 2.2kW, EU

3-phase

Supplied with (Part No)

Connecting sleeve (2129)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2”) 5 m/16 ft (2013)
Floor nozzle B500 mm /W 19.7” (7238)
Suction pipe (Ø50 mm /2”) (7265)
Fine filter, polyester (44017)
HEPA H13 filter (44016)
a-model 5 x plastic bags (42285)

Technical data

HxWxD [mm/in]	1415x600x840/56x23x33
Weight [kg/lb]	a) Container 96/212 c) Bag 92/202 L) Longopac 94/207
Collection container [l/gal]	a) 40/10.6 c) 20/5.3 L) Longopac
Flow max, fan, EU [m³/h]	400
Negative pressure, max, EU [kPa]	30
Power [kW] Power Frequency Converter [kW]	2.2 4
Sound level [dB(A)]	84

DC Storm

Powerful, reliable and safe mobile dust extraction

The DC Storm is a powerful and reliable mobile dust extractor. They are built on a robust and sturdy steel chassis for maximum durability, for example on construction sites. With a direct-driven, three-phase turbopump, the DC Storm is suitable for continuous operation, conveying heavy material away, source extraction and cleaning.

The DC Storm provides sufficient air flow for several users at the same time and it can also be used as a semi-mobile central unit in a tubing system. It is suitable for source extraction for grinding discs up to approx. 800 mm/ 31” in diameter.

Three basic models are available: bag (c), container (a) and Longopac (L), each powered by a 4 kW, 7.5 kW or a 10 hp motor.

The DC Storm 700 is also equipped with a frequency converter, very useful when only 16A are available. This machine is equipped with a PTFE filter extracting large quantities of concrete dust and is suitable for example floor grinding.

Info of all our models – DC Storm 500, DC Storm 600 and DC Storm 700 is presented on the following pages.

Part No DC Storm 500 a/c/L

119400	c 400V /50Hz /4kW
119402	a 400V /50Hz /4kW
119430	L 400V /50Hz /4kW

3-phase



DC Storm 500 With **plastic bag**

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose (Ø50 mm /2”) 7.5 m /22 ft (2401)
Floor nozzle B500 mm /W 19.7” (7238)
Suction pipe (Ø50 mm /2”) (7265)
10 x plastic bags (46145)
Fine filter, polyester (44212)
HEPA H13 filter (42869)

Technical data

HxWxD [mm/in]	1790x780x1160/70x31x46
Weight [kg/lb]	178/392.4
Collection container [l/gal]	60/15.9
Flow max, fan, EU [m^3/h]	500
Negative pressure, max, EU [kPa]	25
Power [kW]	4
Sound level [dB(A)]	75





DC Storm 500 With container

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 7.5 m/22 ft (2013)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Container 75 l /20 US gal (45942)
Fine filter, polyester (44212)
HEPA H13 filter (42869)

Technical data

HxWxD [mm/in]	1790x780x1160/70x31x46
Weight [kg/lb]	180/396.8
Collection container [l/gal]	75/19.8
Flow max, fan, EU [m^3/h]	500
Negative pressure, max, EU [kPa]	25
Power [kW]	4
Sound level [dB(A)]	75

DC Storm 500 With Longopac

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 5 m/16 ft (2013)
Floor nozzle B 500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Longopac 25 m /82 ft (44077)
Fine filter, polyester (44212)
HEPA H13 filter (42869)

Technical data

HxWxD [mm/in]	1790x780x1160/70x31x46
Weight [kg/lb]	178/392
Collection container [mm/ft]	Longopac 25/82 flexible
Flow max, fan, EU [m^3/h]	500
Negative pressure, max, EU [kPa]	25
Power [kW]	4
Sound level [dB(A)]	75

Three-Phase Dust Exctrators

DC Storm 600



DC Storm 600c

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2")
7.5 m/22 ft (2013)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
10 x plastic bags (46145)
Fine filter, polyester (44212)
HEPA H13 filter (42807)

Technical data

HxWxD [mm/in]	1790x780x1160/70.5x31x45.5
Weight [kg/lb]	201/443
Collection container [l/gal]	60/13.6
Flow max, fan, US/CAN [cfm]	353
Negative pressure, max, US/CAN [inwg]	96
Power [hp]	10
Sound level [dB(A)]	75



DC Storm 600a

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2")
7.5 m/ 22 ft (2013)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Container 75 l /20 US gal (45942)
Fine filter, polyester (44212)
HEPA H13 filter (42807)

Technical data

HxWxD [mm/in]	1790x780x1160/70.5x31x45.5
Weight [kg/lb]	203/447.5
Collection container [l/gal]	75/19.8
Flow max, fan, US/CAN [cfm]	353
Negative pressure, max, US/CAN [inwg]	96
Power [hp]	10
Sound level [dB(A)]	75



DC Storm 600L PTFE

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2")
7.5 m/22 ft (2013)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Longopac 25 m /82 ft (44077)
Fine filter, PTFE (44081)
HEPA H13 filter (42807)

3-phase

Technical data

HxWxD [mm/in]	1790x780x1160/70.5x31x45.5
Weight [kg/lb]	201/443
Collection container [mm/ft]	Longopac 20/65 flexible
Flow max, fan, US/CAN [cfm]	353
Negative pressure, max, US/CAN [inwg]	96
Power [kW]	7.4
Sound level [dB(A)]	75

Part No	DC Storm 600c
119407	460V /60Hz /10hp, US
119436	220/380V /60Hz /10hp, US
119408	600V /60Hz /10hp, CAN

Part No	DC Storm 600a
119409	460V /60Hz /10hp, US
119437	220/380V /60Hz /10hp, US
119410	600V /60Hz /10hp, CAN

Part No	DC Storm 600L PTFE
119434	460V /60Hz /10hp, US
119435	220/380V /60Hz /10hp, US

Three-Phase Dust Extractors

DC Storm 700

The DC Storm 700 is also equipped with a frequency converter, very useful when only 16A are available. This machine is equipped with a PTFE filter extracting large quantities of concrete dust and is suitable, for example, floor grinding.



Technical data

HxWxD [mm/in]	1790x780x1160/70x31x46
Weight [kg/lb]	210/463
Collection container [l/gal]	60/15.9
Flow max, fan, EU [m³/h]	700
Negative pressure, max, EU [kPa]	22
Power [kW]	7.5
Sound level [dB(A)]	75

DC Storm 700c

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose (Ø50 mm /2") 7.5 m/ 22 ft (2401)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
10 x plastic bags (46145)
Fine filter, polyester (44212)
HEPA H13 filter (42807)

DC Storm 700a

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 7.5 m/ 22 ft (2013)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Container 75 l /20 US gal (45942)
Fine filter, polyester (44212)
HEPA H13 filter (42807)



Technical data

HxWxD [mm/in]	1790x780x1160/70x31x46
Weight [kg/lb]	214/472
Collection container [l/gal]	75/19.8
Flow max, fan, EU [m³/h]	700
Negative pressure, max, EU [kPa]	22
Power [kW]	7.5
Sound level [dB(A)]	75

DC Storm 700L PTFE

Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 7.5 m/22 ft (2013)
Floor nozzle B500 mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2") (7265)
Longopac 25 m /82 ft (44077)
Fine filter, PTFE (44081)
HEPA H13 filter (42807)



Technical data

HxWxD [mm/in]	1790x780x1160/70x31x46
Weight [kg/lb]	212/467.4
Collection container [l/gal]	Longopac 25/82 flexible
Flow max, fan, EU [m³/h]	700
Negative pressure, max, EU [kPa]	22
Power [kW]	7.5
Sound level [dB(A)]	75

3-phase

Part No DC Storm 700c/a

119403 DC Storm 700c, 400V /50Hz VFD
119418 DC Storm 700a, 400V /50Hz VFD

Part No DC Storm 700L PTFE

119419 400V /50Hz /7.5 kW VFD

Three-Phase Dust Extractors

DC 5900 9.2kW S



This machine is primarily intended to be used for pneumatic conveying or the removal of very heavy material in conjunction with a pre-separator. The extra-large suction capacity can also be utilised for regular source extraction and cleaning, in situations where extra long hoses up to 50 m are required. To prevent overheating during intensive use, the pump has been equipped with a cold air intake.

The reverse pulse filter cleaning system provides extra-long filter life and ensures no loss of suction.

Part No DC 5900 9.2 kW S

119341	a 400V /50Hz
119340	c 400V /50Hz

3-phase

Supplied with (Part No)

Discharge

a) 75 l /19.8 US gal container (45942)
c) 10 x plastic bags (46145)

Fine filter, polyester (429204)
HEPA H13 filter (42807)

Optional HEPA filter:
HEPA H14 filter (42922)

Technical data

HxWxD [mm/in]	1942x780x1160/76x30x45
Weight [kg/lb]	200/440.9
Collection container [l/gal]	a) Container 75/19.8 c) Bag 60/15.9
Flow max, fan, EU [m³/h] Flow max, fan, US/CAN 115V [cfm]	500 294.3
Negative pressure, max, EU [kPa] Negative pressure, max, US/CAN [inwg]	40 161
Power [kW]	9.2
Sound level [dB(A)]	75

DC 5900 9.2kW P



DC 5900 9.2kWP, is a powerful machine with sufficient capacity to support up to three users simultaneously with tasks such as cleaning with Ø38mm cleaning equipment and two more operators with hand-held grinders, saws, drills or with two users with Ø50mm cleaning equipment.

The machine is especially suitable for placed in the basement and with a standing Ø76mm pipe or hose system installed as a riser in stairwells. At each floor, you can then effectively connect the machine's hose through a manifold with flap valve.

Part no DC 5900 9.2kW P a/c/L

119301	a 60 l bag
119305	c 75 l container
119333	L Longopac
119336	L 460V /15hp 60Hz, US/CAN
119314	c 460V /15hp 60Hz, US/CAN
119315	a 460V /15hp 60Hz, US/CAN
119316	c 600V /15hp 60Hz, US/CAN
119317	a 600V /15hp 60Hz, US/CAN

3-phase

Supplied with (Part No)

Discharge

a) 75 l /20 US gal container (45942)
c) 10 x plastic bags (46145)
L) Longopac 25 m /82 ft (44077)

Fine filter, polyester (4292)
HEPA H13 filter (42807)

Optional HEPA filter:
HEPA H14 filter (42922)

Technical data

HxWxD [mm/in]	1942x780x1160 /76x30x4
Weight [kg/lb]	210/463
Collection container [l/gal]	a) Container 75/19.8 c) Bag 60/15.8 L) Longopac
Flow max, fan, EU [m³/h] Flow max, fan, US/CAN [cfm]	800 470.9
Negative pressure, max, EU [kPa] Negative pressure, max, US/CAN [inwg]	28 112
Power [kW]	9.2
Sound level [dB(A)]	75

Accessoires for DC 5900 L 9.2 kW P (Part No)

Adaption Kit for Longopac (44248)



Supplied with (Part No)

Suction hose, antistatic, 5 m/16 ft (Ø50 mm /2") (2013)
Floor nozzle B500 mm/19.7" (7238)
Suction pipe (Ø50 mm/2") (7265)
Connecting sleeve (2129)
Coupling socket (2008)
Fine filter, polyester (44017)
HEPA H13 filter (44016)

Collecting variations:

a-model, Steel container with 5 x plastic bags (42285)
c-model, Intellibag ,10 x roll (43619)
L-model, Longopac Mini Superstrong 4 x 23 m (432177)



Part No DC 5900H Asbestos

119370	400V /4 kW 50 Hz
119350	400V /9.2 kW P 50 Hz
119360	400V /9.2 kW S 50 Hz

3-phase

DC Tromb Turbo VFD Asbestos

CAUTION
ASBESTOS REMOVAL IN PROGRESS

We are expanding our Asbestos-line of dust extractors with 3 new machines: Tromb H Asbest Turbo VFD. This solution is especially developed for asbestos dust extraction that demands long operation times in large construction sites. The DC Tromb Turbo Asbestos is certified by the IFA* for asbestos removal. If you require exra long hose lenght for your asbestos operations, Tromb H Asbest Turbo VFD is the best choice. This powerful machine can be ordered with different selection of collection containers:

a) Steel container
c) Plastic bag - Intellibag
L) Logongopac

Technical data

HxWxD [mm/in]	1390x600x840/55x23x33
Weight [kg/lb]	96/212 92/203 94/207
Collection container [l/gal]	40, 20, Longopac
Flow max, fan, EU [m^3/h]	400/235
Negative pressure, max, EU [kPa]	30/120
Power Frequency Converter[kW]	4
Power Turbopump[kW]	2.2
Sound level [dB(A)]	84

Part No DC Tromb Turbo VFD Asbestos

176000	a 2.2KW/4HP EU
176100	c 2.2KW/4HP EU
176200	L TURBO VFD 2.2KW/4HP EU

3-phase

DC 5900 H Asbestos

All DC 5900s are powerful and reliable mobile dust extractors. They are built on a robust and sturdy steel chassis for maximum durability. Now also for work in hazardous enviroments. The DC 5900 H Asbestos is certified by the IFA* for asbestos removal. Don't take risks with your health when removing asbestos!

4 kW Supplied with (Part No)

Coupling socket (2107)
Coupling socket (2008)
Suction hose antistatic (Ø50 mm /2") 7.5 m /22 ft (2013)
Floor nozzle B 500mm /W 19.7" (7238)
Suction pipe (Ø50 mm /2")(7265)
Plastic bag (46141)
Fine filter, polyester (4292)
HEPA H13 filter (42869)
Container 75 l /19 US gal (7368)

9.2 kW P & S Supplied with (Part No)

Fine filter, polyester, 9.2 kW S (4292)
Fine filter, polyester, 9.2 kW P (429204)
HEPA H13 filter (42807)

Technical data	4 kW	9.2 kW P	9.2 kW S
HxWxD [mm/in]	1940x780x1160/76x30x45	1940x780x1160/76x30x45	1940x780x1160/76x30x45
Weight [kg/lb]	176/388	210/462	210/462
Collection container [l/gal]	75/19.8	75/19.8	75/19.8
Flow max, fan, EU [m^3/h/cfm]	470/353	800/471	500/294
Negative pressure, max, EU [kPa/inwg]	28/112	28/112	40/160
Power [kW]	4	9.2	9.2
Sound level [dB(A)]	75	75	75

*The dust extractor has been DGUV tested and approved by IFA (Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung).




Dustcontrol
STORM 700
H
Dustcontrol
STORM
Part no 4613
intbar

Compare our Dust Extractors

1-phase **Dust extractor** with one-motor

Technical data mini	DC 1800	DC 1800XL	DC 2900 c/a	DC 1800/2800 H Asbestos
HxWxD [mm/in]	780x405x390/31x16x15	1160x380x380/46x15x15	c) 1110x445x570/44x17x22	1800) 740x380x380/29x15x15
HxWxD [mm/in]			a) 1145x445x630/45x17x25	2800) 1110x440x550/43x17x21
Weight [kg/lb]	14/31	19/42	c) 16/35 a) 22/48	1800) 14 /31 2800) 19 42
Hose length Ø38 mm /1.5" [m/ft]	5/16	5/16	5/16	
Collection container [l/gal]	20/5.2	60/15.9	c) 20/5.3 a) 40/10.6	1800) 20/5.3 2800) 40/10.6
Flow max, fan, EU [m³/h]	205	205	205	205
Flow max, fan, UK 115V/230V [m³/h]	190/205	190/205	190/205	
Flow max, fan, US/CAN 115V [cfm]	126.5	126.5	126.5	126.5
Negative pressure, max, EU/UK [kPa]	24	24	24	21/24
Negative pressure, max, US/CAN [inwg]	84	84	96	96
Power 115/230V [W]	1340/1285	1340/1285	1284/1285	1340/1285
Sound level [dB(A)]	68	68	68	1800) 68 2800) 70
Filter area, fine/HEPA filter	1.5 m²/0.85 m², 16 ft²/9.1 ft²	1.5 m²/0.85 m², 16 ft²/9.1 ft²	1.5 m²/0.85 m², 16 ft²/9.1 ft²	1.5 m²/0.85 m², 16 ft²/9.1 ft²

1-phase **Dust extractor** with twin-motor


Technical data midi	DC Tromb H 400 a/c/L	DC Tromb H 400 Twin c/L	DC Tromb H 400 Asbestos	DC Chip Extractor
HxWxD [mm/in]	1390x600x780/55x23x31	1390x600x1280/55x23x50	1390x560x70/55x22x27	1530x600x780/60x23.5x31
Weight [kg/lb]	a) 50/110.2 c) 46/101.4 L) 50/110.2	cc) 71/168 cL) 80/173	50/110	69/152
Hose length Ø38 mm /1.5" [m/ft]	5/16	5/16	5/16	7.5/22
Collection container [l/gal]	a) 40/10.6 c) 20/5.3 L) Longopac	c) 20/5.3 L) Longopac	40/10.6	90/24
Flow max, fan, EU [m³/h]	420	420	393	355
Flow max, fan, UK 115V/230V [m³/h]	360/420	360/420		
Flow max, fan, US/CAN 115V [cfm]	212	212	231	
Negative pressure, max, EU/UK [kPa]	21 (+/- 10%)	21 (+/- 10%)	21/24	22
Negative pressure, max, US/CAN [inwg]	84	84	88	88
Power 115/230V [W]	2100/2680/3000	2100/2680/3000	3000	2600
Sound level [dB (A)]	70	70	70	70

3-phase **Dust extractor**

Technical data	DC Tromb Turbo VFD	DC Tromb Turbo Direct start	DC 5900 9.2 kW S	DC 5900 15 hp kW P
HxWxD [mm/in]	1390x600x840/55x23x33	1390x600x840/55x23x33	1942x780x1160/76x30x45	1942x780x1160/76x30x45
Weight [kg/lb]	a) 88/194 c) 84/185 L) 86/190	a) 6/212 c) 92/202 L) 94/207	200/440.9	210/463
Hose length Ø38 mm /1.5" [m/ft]	5/16	5/16	5/16	5/16
Collection container [l/gal]	a) 40/10.6 c) 20/5.3 L) Longopac	a) 40/10.6 c) 20/5.3 L) Longopac	a) 75/19.8 c) 60/15.8 L) Longopac	a) 75/19.8 c) 60/15.8 L) Longopac
Flow max, fan, EU [m³/h]	260	400	500	800
Flow max, fan, UK 115V/230V [m³/h]				
Flow max, fan, US/CAN 115V [cfm]	186		294.3	470.9
Negative pressure, max, EU/UK [kPa]	28	30	40	28
Negative pressure, max, US/CAN [inwg]	112	120	161	112
Power 115/230V [kW]	2.2	2.2	9.2	15 hp
Sound level [dB(A)]	72	84	75	75
Filter area, fine/HEPA filter	3.6 m²/3.0 m² 39 ft²/32.3 ft²	3.6 m²/3.0 m² 39 ft²/32.3 ft²	.6 m²/3.0 m² 39 ft²/32.3 ft²	3.6 m²/3.0 m² 39 ft²/32.3 ft²

Pressure generation and airflow of our machines


kPa vs m³/h



kPa vs m³/h

1. DC 1800 H, DC 1800 XL, DC 2900
2. DC Chip Extractor
3. DC Tromb H 400
4. DC Tromb Turbo – Direct Start
5. DC Tromb Turbo – Frequency Converter
6. DC 5900 9.2kW S
7. DC 5900 9.2kW P
8. DC Storm 500
9. DC Storm 600
10. DC Storm 700

cfm vs inwg



cfm vs inwg

1. DC 1800 H, DC 1800 XL, DC 2900
2. DC Chip Extractor
3. DC Tromb H 400
4. DC Tromb Turbo – Direct Start
5. DC Tromb Turbo – Frequency Converter
6. DC 5900 9.2 kW S
7. DC 5900 9.2 kW P
8. DC Storm 500
9. DC Storm 600
10. DC Storm 700

3-phase **Dust extractor**

Technical data	DC Storm 500 c/a/L	DC Storm 600 c/a/L	DC Storm 700 c/a/L
HxWxD [mm/in]	1790x780x1160/70x31x46	11790x780x1160/70x31x46	11790x780x1160/70x31x46
Weight [kg/lb]	c) 178/392.4 a) 180/396.8 L) 178/392.4	c) 201/443 a) 203/447.5 L) 201/443	c) 210/463 a) 214/472 L) 212/467.4
Hose length Ø38 mm /1.5" [m/ft]	5/16	5/16	5/16
Collection container [l/gal]	c) 60/15.9 a) 75/19.8 L) 20/65 flexible	c) 60/15.9 a) 75/19.8 L) 20/65 flexible	c) 60/15.9 a) 75/19.8 L) 20/65 flexible
Flow max, fan, EU [m³/h] Flow max, fan, UK 115V/230V [m³/h]	500		700
Flow max, fan, US/CAN 115V [cfm]		353	
Negative pressure, max, EU/UK [kPa]	25		22
Negative pressure, max, US/CAN [inwg]		96	
Power 115/230V [Kw]	4	10	7.5
Sound level [dB(A)]	75	75	75
Filter area, fine/HEPA filter	5 m²/2.7 m² 54 ft²/29 ft²	5 m²/2.7 m² 54 ft²/29 ft²	5 m²/2.7 m² 54 ft²/29 ft²

Semi-Mobile Systems



A semi-mobile system increases the accessibility to a powerful dust extractor on each floor. Instead of moving several small and large dust extractors around, multiple users can simultaneously connect their machines or power tools via a hose to a connection point.

Semi-Mobile Systems

Semi-mobile dust collection systems are a practical solution when work is to be carried out on several floors and by several users at the same time. Each floor is connected to a central extraction system via a hose connection package and is equipped with a connection point for connecting the suction hose to the machine being used.

A Ø76 mm /3” hose that forms the main line is taken up through, for example, a lift shaft, refuse disposal chute or stairwell, and run to the dust extractor, which can in turn be connected to a pre-separator to collect larger particles, if necessary. One package is used for each floor to facilitate installation.
The sound level is reduced and it becomes easy for each team to clean up regularly, once the task has been completed.



The Branch Pipe and Hose Connection Package (Prod No 3353) consists of

1 x Rubber plug with chain	(4016)
1 x Hose, 2.5 m, 76 l	(2024)
2 x Joint Ø76 mm /3” (remove rubber ring)	(3007)
2 x Tube Ø76 mm /3” * 135	(3341)
1 x Screw 6*40	(MC6S)
1 x Branch pipe 45°, Ø76 mm /3”	(300311)
1 x Flap valve Ø50/76 mm /2”/3”	(3006)

The Start Box (Prod No 8178)


The Hose Connection Package does not include electrical cables or the Start Box for vacuum producers (ordered separately).

The Start Box	(8178)

Simultaneously Dust Extraction.
Several users can simultaneously connect their machines or power tools via the hose connection point.

One **Hose Connection Package** is used for each floor.

The **Start Box** is placed at the base level.



Hose Connection Package Part No 3353



Start Box Part No 8178



Powerful Dust Extraction
DC 5900 Part No 119320
DCF Storm Part No 70701





Wet-Vacs

for those of you who deal with larger quantities of water, we have developed a line of professional wet-vacs that can handle the toughest environments.

Wet-Vacs

DC 50W



When drilling in concrete, large quantities of water are required, which becomes very dirty. Using a wet-vac to effectively extract the water prevents both the workplace from becoming wet and dirty, and the sewerage system from silting up. The slurry solids are collected in a filter bag for easy handling and disposal.

Dustcontrol's wet-vacs are easy to disassemble for cleaning and decontamination. This is an important benefit on units that require frequent cleaning. Robust construction helps these units resist the knocks from everyday use.

Supplied with (Part No)

Coupling socket (2108)
Connecting sleeve (2114)
Suction hose Ø38 mm /1.5", 5 m /16ft, antistatic (2012)
Floor nozzle B370mm /W14"(7236)
Suction pipe Ø38, aluminium (7258)
Filter bag (42190)

Part No DC 50 W

118600	230V /50Hz, EU
118610	230V /50Hz, EU, without pump

1-phase

Technical data DC Wet-Vac 50 W

HxWxD [mm/in]	870x630x543/ 34x25x21
Weight [kg/lb] with pump /without pump	43/95 30/66
Collection Container [l/gal]	50/13
Hose length Ø38 mm /1.5" [m/ft]	5/13.2
Flow max, open inlet EU [m^3/h]	190
Negative pressure, max, EU [kPa]	21
Power [W] Vacuum motor, single-phase 230V	1285
Pump, single-phase [W]	550
Sound level [dB(A)]	75

DC 75W



Supplied with (Part No)

Coupling socket (2108)
Connecting sleeve (2115)
Suction hose Ø38 mm/1.5", 5 m /16ft, antistatic (2012)
Floor nozzle B370mm /W14"(7236)
Suction pipe Ø38, aluminium (7258)
Filter bag (42190)

Part No DC 75 W

118700	230V /50Hz, EU
118710	230V /50Hz, EU, without pump

1-phase

Technical data DC Wet-Vac 75 W

HxWxD [mm/in]	980x630x550/ 38x25x21
Weight [kg/lb] with pump /without pump	45/99 32/70
Collection Container [l/gal]	75/19.8
Hose length Ø38 mm /1.5" [m/ft]	5/16
Flow max, open inlet EU [m^3/h]	190
Negative pressure, max, EU [kPa]	21
Power [W] Vacuum motor, single-phase 230V	1285
Pump, single-phase [W]	550
Sound level [dB(A)]	75

Updates of DC Wet-Vac 75 W

Our DC 50W and DC 75W liquids extractors have been updated with a smaller electrical connector between the motor top and the pump. And a drain valve to easily drain water.

Note! When purchasing spare parts for the engine top for previous models (with a blue and larger electric connector), order part no 432138. The new motor top (with black and small electric connector) has part no 432138-1.






Dustcontrol

Air Cleaners



Air Cleaner

DC AirCube 600

This air cleaner combines ergonomic design with powerful performance – and which, thanks to its low weight, is easy to carry and move when needed. With an adjustable airflow, operation is easily adapted to different areas of use.

The generous filter area ensures a long service life and optimal filtration, while the lockable power cable contributes to increased safety during use. An integrated operating time meter provides full control over use and service intervals.

For increased functionality, the unit is equipped with a device socket. In addition, the design is stackable.

Part No DC AirCube 600

112600	230V /50Hz, EU
112601	230V /50Hz, UK
112608	230V /50Hz, CH
112509	230V /50Hz, AU

1-phase

SCAN ME

Technical data

HxWxD [mm/in]	370x304x430/ 14.57x11.97x16.93
Weight [kg/lb]	10/22
Inlet Ø [mm/in]	200/7.9
Outlet Ø [mm/in]	200/7.9
Flow max, fan 230V (EU/US,CAN) [m^3/h/cfm]	600/353.1
Power, fan 230V (EU) [W]	170
Pre-filter area [m^2/ft^2]	0.71/7.64
HEPA filter area [m^2/ft^2]	4.47/48.11
Filter class	HEPA H13
Sound level [dB(A)]	0-75

Supplied with (Part No)

HEPA H13 Filter (46378)
Pre-Filter G4 AC600 (46395)





Accessories (Part No)



Ceiling Mounting AC600
(46433)



Funnel Connection D200 AC600
(46429)

Ventilation Kit D200 AC600
(46434)



Pre-Filter G4
(46395)

HEPA H13 Filter
(46378)

DC AirCube 1200

The DC AirCube 1200 is a highly efficient and robust air cleaner with the ability to clean the air even in large rooms, at a rate of up to 1060 m³/h /624 cfm. The encapsulated fan housing contains a radial blower type fan that builds up high pressure across its entire flow range, which provides effective air cleaning for the entire lifetime of the filter. The speed of the fan is also continuously variable in order to save energy. The DC AirCube 1200 is equipped with both a HEPA H13 filter that captures the smallest particles and a light that indicates when it is time to replace the filter.



Part No DC AirCube 1200

103100	230V /50Hz, EU
103101	230V /50Hz, UK
103102	115V /50Hz, UK
103103	115V /60Hz, US/CAN
103108	230V /50Hz, CH
103109	230V /50Hz, AU

1-phase

Supplied with (Part No)

HEPA H13 filter (42940)
Pre-filter (42918)

Optional HEPA filter:
HEPA H14 filter (42924)

Accessories (Part No)

Hose kit (42657)
Bend 90° (42660)
Transport cover (45170)

Technical data

HxWxD [mm/in]	930x520x650/ 37x21x26
Weight [kg/lb]	23/51
Inlet/Outlet Ø [mm/in]	250/315 10/12.4
Power, fan 115/230 [W]	340/500
Flow max, open inlet 230V [m³/h/cfm]	1060/624
Pre-filter area [m²/ft²]	0.40/4
HEPA filter area [m²/ft²]	5/54
Filter class	H13
Sound level [dB(A)]	60-68

DC AirCube 2000

With a capacity of approximately 1.850 m³/h /1089 cfm the DC AirCube 2000 is the Dustcontrol´s most powerful cleaner. The DC AirCube 2000 has a robust, stainless-steel chassis and an encapsulated fan with variable speed setting. With its ergonomic design, it is easy to carry and transport. It can also be operated when positioned horizontally.

The DC AirCube 2000 has a HEPA H13 filter with an area totalling 10 m² /107 ft². An integrated light indicates when it is time to replace the filter.



Part No DC AirCube 2000

103000	230V /50 Hz, EU
103002	230V /50 Hz, UK
103003	115V /50 Hz, UK
103004	115V /60 Hz, US/CAN
103008	230V /50 Hz, CH
103009	230V /50Hz, AU

Supplied with (Part No)

HEPA H13 filter (42896)
Pre-filter (42917)

Optional HEPA filter:
HEPA H14 filter (42923)

Accessories (Part No)

Hose kit (42657)
Bend 90° (42660)
Transport cover (45170)

Technical data

HxWxD [mm/in]	1020x520x650 /41x21x26
Weight [kg/lb]	30/67
Inlet/Outlet Ø [mm/in]	315/315 12.4/12.4
Power, fan 115/230 [W]	375/750
Flow max, open inlet 230V [m³/h/cfm] max	1850/1089
Pre-filter area [m²/ft²]	0.6/6
HEPA filter area [m²/ft²]	10/108
Filter class	H13
Sound level [dB(A)]	60-68

1-phase


Dustcontrol




Decontamination Systems

DC Box

The DC Box is a especially designed dust extraction cabinet that protects against hazardous dust during decontamination and cleaning before servicing or repairing machines and tools. The DC Box is equipped with a blow gun and a suction hose for vacuum cleaning. Larger particles and debris fall down into the collection container a plastic bag attached to the bottom of the cabinet.

The DC Box is easy to work with. Tools and machines are placed onto the rotating worktable and slid in through the side door. These are then cleaned either by vacuuming or using compressed air. The fine dust is vacuumed up and transported away via a tubing system to a complete central unit located either in- or outdoors.



DC Box DCF Tromb DC 11-Module

Installation example for our DC Box.

Standard or Custom?

The DC Box is available in two versions: Standard and Custom:

DC Box Standard is the ideal solution for most users. This solution has now been updated with a selection of 3 discharge options: Container (A), Intelli-bag (C) or Longopac (L) as standard.

Some more new features of DC Box Standard:

• The outlet on the top of the DC-Box has been enlarged to D108 instead of the previous D76.

• The user can adjust the working height as the legs are now adjustable.

• The outer dimensions of the box have also been adjusted to fit on a standard European pallet. Safer and more cost-effective transportations!

DC Box Custom. If you want to be able to roll taller equipment directly into the cabinet for decontamination, then the DC Box Custom is the solution for you. DC Box Custom is customised after your requirements.

The size of the central unit and dimensioning of the tubing system is tailored to the needs of the projects. The system can be expanded so that it can also be used as a central extraction system with connections that are easily accessible across the entire worksite.



DC Box Custom

DC BOX Custom (Part No)
Part no 7470 DC BOX
Part no 72014 TROLLEY
Part no 7999 DC BOX CUSTOM

Contact our sales representative for a quotation DC Box Custom.

Compact Vacuum Systems



DC Box Standard



DC BOX Standard (Part No)

Part no 7480 DC BOX STANDARD A
Part no 7481 DC BOX STANDARD C
Part no 7482 DC BOX STANDARD L

UPDATES

The former solution DC Box Compact is discontinued. In the DC Box Compact solution a DC AirCube 500 was connected as standard. However if ventilation of the DC Box with an air cleaner is desired, it can be connected to the D108 outlet of our new solution DC Box Standard. Shutter valves and tubing systems that previously came as standard for DC Box Standard will now have to be selected separately instead.


TECHNICAL DATA	DC Box Standard
HxWxD [mm/in]	1620-1770 x 1155 x 760 / 63.8 - 69.7 x 45.5 x 30
Weight [kg/lb]	160/353
Outlet Ø [mm/in]	108 x 1. 50 x 1 / 4.25 x 1. 2 x 1
Nominal pressure drop [kPa] / [inwg]	3.5 / 14.1
Nominal flow [m3/h] / [CFM] (EU) [m^3 / h] / (US / CAN) [CFM] [m^3/h /cfm]	700 / 412
Voltage [V]	230



Compressed air connection and blow gun nozzle. Suction hose for easy cleaning inside the cabinet.



DC Box Standard



DC Box Custom



Pre-Separators

About Pre-Separators

Pre-Separators can be used in all applications where the extracted material is coarse or voluminous. These can be placed in the actual workplace for separate handling or recovery of the extracted material, or centrally to relieve filter loading.

Pre-Separators separate material from the air flow using the action of a cyclone or with inertial separation.

The Cyclone Principle is very effective in separating particles down to 1/100 mm.

Inertial separators are generally configured as containers with the inlet and outlet in the same wall of the container. When the air flow changes direction abruptly, separation occurs for the particles with higher relative mass.

Cyclone Pre-Separators

TYPE OF MATERIAL	Air flow [m³/h]	Select Pre-Separator
All types, particularly where	100–200	DCF 60, F 2500, DCF 2800
a large percentage is fine	100–500	DCF Mobil
particulate	200–500	F 3500
	500–700	F 8000
	500–1000	F 11000
	1000–4000	F 20000
	2000–5000	F 30000

DISCHARGE TO	Volume	Equipment
Plastic bag	lesser	Discharge cone
Compacted in plastic bag	greater	Auger Compactor
Open Container, Conveyor	lesser	Foot Valves/Auto Foot Valve/
		Discharge Valves
	greater	Peristaltic Airlock
Small Container	lesser	With or without plastic bag
Tipping Container	greater	




Cyclone Principle

Meaning that the inlet is mounted tangentially on the body and the air flow is thus forced against the inside of the cyclone.

Inertial Pre-Separators

MATERIAL TYPE	Air flow [m³/h]	Volume	Select Pre-Separator
Coarse and dense	250-2000	moderate	Tipping Container
	250-2000	large	Large Container



Inertial Principle

Meaning that the air stream flows into the container and abruptly changes course.

DCF **Tromb**

The DCF Tromb a/c/L is ideal for floor grinding and semi-mobile systems where large quantities of dust are handled. The pre-seperator reduces the strain on the extraction source and is equipped with a intellibag/Longopac/container-solution for dust-free bag replacement, therefore allowing the user to avoid unnecessary and time-consuming shutdowns.

TECHNICAL DATA	DCF Tromb
HxWxD [mm/in]	1290x600x780/53.5x23.5x31.5
Weight [kg/lb]	A) 33/73 L) 32/70 C) 27/59
Inlet Ø [mm/in]	76/3
Collection container [l/gal]	A) 40/10.6 C) 20/5.3 L) Longopac
Air flow [m³/h / cfm]	400–700/235-412



Part No	Description
707002	DCF Tromb a
707001	DCF Tromb c
707000	DCF Tromb L

Supplied with (Part No)

DCF Tromb A
5 x plastic bags (42285)

DCF Tromb C
10 x plastic bag (43619)

DCF Tromb L
Longopac (432177)

DCF **Storm**

The DCF Storm is ideal for floor grinding and semi-mobile systems and could be set apart to handle large and heavy quantities of dust. The pre-separator relieves the loading on the filter in the vacuum source and is equipped with a Longopac solution for dust-free bag changing, so that the user can minimise unnecessary and time-consuming stoppages. Also available as a standard “c” model with an intellibag.

TECHNICAL DATA	DCF Storm
HxWxD [mm/in]	185x70x108 /73x27x42
Weight [kg/lb]	46/101
Inlet Ø [mm/in]	108/4
Flow max, fan, EU [m³/h] Flow max, fan, US/CAN [cfm]	700 412



Part No	Description
70700	DCF Storm c
70701	DCF Storm L

Supplied with (Part No)

DCF Storm c
plastic bags (46145)

DCF Storm L
Longopac 25 m /82 ft
(44077)

DCF **Cyclone Separator Cover**

When large quantities of dust are produced, a DC 5900, for example, can be supplemented with a cyclone separator cover that is fitted directly onto a standard barrel.

Part No	Description
7367	Cyclone separator cover

TECHNICAL DATA	DCF Cyclone Separator Cover
HxWxD [mm/in]	580/23
Weight [kg/lb]	10/22
Inlet/Outlet Ø [mm/in]	76/3
Cyclone diameter Ø [mm/in]	Ø250/10
Barrel diameter Ø [mm/in] (For a standard barrel 200/52.8 [l/gal]	620/24



DCF **60**

The DCF 60 Pre-Separator can handle large quantities of dust. Due to its large inlet the Pre-Separator is also well suited to separate coarse dirt. Perfect for wood floor grinding.

Part No	Description
7069	DCF 60 with wheel set

TECHNICAL DATA	DCF 60
HxWxD [mm/in]	1060x380x380/42x15x15
Weight [kg/lb]	10/22
Inlet Ø [mm/in]	Ø62 /2.4
Outlet Ø [mm/in]	Ø50 /2
Collection container [l/gal]	55/14.5
Air flow [m³/h / cfm]	100–200/59-118



DCF **2900 c/L**

The DCF 2900 Pre-Separator is often used in combination with the DC 2900 dust extractor to relieve the loading on the filter. Two models available, with bags (c) or with Longopac (L).

Part No	Description
7372	DCF 2900 c
737200	DCF 2900 L

TECHNICAL DATA	DCF 2900 c/L
HxWxD [mm/in]	1000x540x450/39x21x18
Weight [kg/lb]	c) 10/22 L) 15/33
Inlet Ø [mm/in]	Ø50/2
Cyclone diameter [mm/in]	Ø250/10
Collection container [l/gal]	c) 40/10 L) Longopac
Air flow [m³/h / cfm]	100–200/59-118



Supplied with (Part No)

42702 Plastic Bags
44763 Longopac mini, 7 x 12 m/39ft



DCF **Wheelbarrow**

The DCF Wheelbarrow is a mobile pre-separator designed like a wheelbarrow for ease of use. A small cyclone with two inlets is fitted in the container. Two tools, cleaning implements etc. can be connected at the same time. The container also has a special hatch so that material can be shovelled in and out.



TECHNICAL DATA	DCF Wheelbarrow
HxWxD [mm/in]	1200x1350x640 /47x53x25
Weight [kg/lb]	50/110
Inlet/Outlet Ø [mm/in]	Ø76/3
Cyclone diameter Ø [mm/in]	Ø250/10
Filling volume [l/gal]	120/32

Part No	Description
7130	DCF Wheelbarrow

DCF **Tipping Container**

Tipping containers can be used as inertial separators by equipping the container with a divider baffle and fitting hoses onto the inlet/outlet connections on the rear wall of the container.

Inertial separation is particularly suitable when large quantities of coarse material are involved.



Part No	Description
7196	0.6 m³/158 gal
7198	2.5 m³/660 gal

TECHNICAL DATA	DCF Tipping Container 0.6m³/158 gal
HxWxD [mm/in]	1180x1080x1590 /46x42x62
Weight [kg/lb]	240/529
Total volume [m³/gal]	0.6/158
Filling volume [m³/gal]	0.3/79
Negative pressure, max [kPa/inwg]	40/160

TECHNICAL DATA	DCF Tipping Container 2.5m³/660 gal
HxWxD [mm/in]	147x128x218 /58x50x86
Weight [kg/lb]	570/1257
Total volume [m³/gal]	2.5/660
Filling volume [m³/gal]	1.3/343
Negative pressure, max [kPa/ inwg]	40/160



The most hazardous dust is the dust you can’t see.

The smaller a particle is, the deeper into the pulmonary system it penetrates. Respirable dust, the dust we inhale, is made up of particles smaller than 5 thousands of a millimetre (5 µm). Because the particles are so small, they can penetrate into the deepest parts of the pulmonary system where the air moves too slowly to be able to breathe them out again.

The lungs’ way of protecting themselves is to wrap the foreign particles in nodules of connective tissue, which, in time, leads to pneumoconiosis or COPD (Chronic Obstructive Pulmonary Disease). Some types of particles, such as silica and asbestos dust, cannot be broken down by the body and are also sharp, which is why they continue to cause damage long after they have become lodged in the lungs.

The best protection is to remove dust at the source and never allow it to reach the air. Dustcontrol has developed suction casings for most handheld and stationary machines, and also produces tailor-made suction casings.

Classification of Dust Extractors and HEPA Filters

Dust extractors are used to improve the working environment, and to reduce levels of hazardous dust in the air to a minimum. This places great demands on the ability of the dust extractor to separate fine dust. We use a fine filter in our mobile dust extractors, which separates most of the dust. But in order to capture close to 100% of the finest and most dangerous particles, we always complete the design with a HEPA H13 filter.

Here at Dustcontrol, we use conical pleated filters in all of our dust extraction units. A pleated filter has a very large area in relation to its physical size. The dust extractors can therefore be compact in relation to the large filter area they contain.

Only original Dustcontrol filters are tested and approved for use in our machines. The use of other types of filters could lead to the leaking of hazardous dust and/or machine breakdown. Dustcontrol's warranty only applies to machines equipped with original Dustcontrol spare parts. The filters are certified in accordance with current European requirements for dust extraction. This ensures that, with correct handling, optimum filtration will be achieved. Follow the instructions when handling filters, so that they can be replaced without exposure to hazardous dust.

To ensure that the filters comply with the requirements of relevant regulations for health and safety at work, a number of different testing standards are used. These are described below:

Test methods

The test methods used in current standards for dust extractors and filters are always based on particle counting. By injecting particles before the filter and by using a particle counter to determine the concentration before and after the filter, the penetration can be calculated (a penetration of 0.1% is equal to a degree of separation of 99.9%). The test is carried out in several stages by individually examining the filter media, the complete filter cartridge and, in some cases, also the complete unit.

HEPA filters — High Efficiency Particulate Air Filters

When classifying HEPA filters, Dustcontrol uses the strict HEPA standard (EN 1822-1). It is divided into different levels (E10 to H14) depending on filtration efficiency. Dustcontrol applies level H13, which can separate up to 99.95% of the particles between 0.15 and 0.30 µm in size. This particle size is used because it is the hardest to separate – both larger and smaller particles are easier to capture in a filter.


Dust extractors

In IEC-60335-2-69 (EN-60335-2-69), the standard for testing wet and dry extractors, dust extractors are classified into three categories – **L for low, M for medium and H for high** – where the H category is the most stringent. (Please note: do not confuse this "H" with that in HEPA H13). The category required for a specific application is decided on the basis of the permitted maximum concentration for that type of dust (MAK) in the working environment or by local regulations.

The test according to EN-60335-2-69 comprises two parts:

1. A test of the filter system – in our case, a fine filter and a HEPA H13 filter. To achieve category H, a degree of separation of 99.995% is required, where 90% of the test particles must be smaller than 1.0 µm. Our fine filters comply with category M, and our HEPA H13 filters with category H.

2. A test of the "assembled unit" – in our case, a complete dust extractor. Here, 99.995% efficiency is also required, however 10% of the particles must be smaller than 1.0 µm, 22% smaller than 2.0 µm, and 75% smaller than 5.0 µm.



Dustcontrol's high-efficiency air cleaner – the DC AirCube – is equipped with a HEPA H13 filter to separate dust and particles down to 0.3 microns. The DC AirCube contributes to a healthier working environment.

Classification of our Dust Extractors

NAME	CLASSIFICATION	STANDARD	EFFICIENCY	PARTICLE SIZE	EXAMPLE	MAK (Maximum Work-place Concentration)
	L= 		> 99%			> 1.0 mg/m³
	M= 		> 99,9%			> 0.1 mg/m³
IEC* standard	H= 	IEC 60335-2-69	> 99.995%	0.1 - 5.0 µm**	H=99.995%	< 0.1 mg/m³ and carcinogenic substances including asbestos

* IEC: International Electrotechnical Commission

** Part 1: 90 % < 1.0 µm

Part 2: 10 % < 1.0 µm
22 % < 2.0 µm
75 % < 5.0 µm

Classification of our HEPA filters

NAME	CLASSIFICATION	STANDARD	EFFICIENCY	PARTICLE SIZE	EXAMPLE
	E10		85%	MPPS** between 0.15–0.30 µm	
	E11		95%		
	E12		99.5%		
HEPA*	H13	EN 1822-1	99.95%		HEPA H13 = 99.95 %

* High Efficiency Particle Air filter, ** Most Penetrating Particle Size

Introduction to HEPA 14 filters

HEPA H14 is now available for our air cleaners and some of our mobile dust extractors

We have introduced a number of H14 filters in in our assorment of filters, and when ordering these a certificate is included. See list to the right.

Please note! Our dust extractors will continue to be delivered with H13 filters, but if desired, the customer can order a filter of the H14 class.

Part no 42926 HEPAFILTER
DC1800/DC2900 H14

Part no 42921 HEPAFILTER
DC5900 4KW/5KW/5,5KW HEPA 14

Part no 42922 HEPAFILTER
DC5900 9,2KW H14

Part no 42925 HEPAFILTER
AIRCUBE 500 H14

Part no 42924 HEPAFILTER
AIRCUBE 2000 CONICAL H14

Part no 42923 HEPAFILTER
AIRCUBE 1200 H14

Accessories and Hoses



In order for you to get the most out of your Dustcontrol, you need the right accessories. We supply cleaning equipment in all sorts of designs and materials. If something is missing, we can even manufacture customised solutions. Please speak to your sales representative for more information.

Cleaning accessories Ø38 mm /1.5"



No	Part No	Description
1	7038	Suction nozzle
2	7047	Suction brush W 200 mm /7.8"
3	7048	Pipe nozzle RB 100
4	7049	Pipe nozzle RB 200
5	7276*	Tapered nozzle
6	7365	Flat nozzle
7	7257	Suction pipe Ø38 mm/ 1.5"
8	7258	Aluminium wand
9	7259	Aluminium wand, with wear strip
10	7260	Chrome steel extension wand, L = 715 mm /28"
11	7261	Aluminium extension wand, L = 705 mm /27"
12	7264*	Tapered nozzle
13	7213	Chrome steel flat nozzle, L = 400 mm /15.7"
14	7035	Chrome steel hand pipe
15	7262	Chrome steel hand pipe, curved
16	7235*	Cast aluminium floor tool 370 mm /14.5"
17	7236*	Cast aluminium floor tool 450 mm/ 17.7"
18	7320/21	Moulded plastic floor tool 320 mm /12.6", with rubber wipe/brush
19	7322/23	Moulded plastic floor tool 370 mm /14.5", with rubber wipe/brush
20	7300	Rubber floor tool
21	7278*	Suction brush
22	7275	Rubber part of suction brush, 7278
23	7263	Brush for 7275, 7278
24	726301	ESD brush for 7278, 7279
25	7398	Brush for 7278, 7279, hard, white
26	7237*	Cast aluminium floor tool 370 mm /14.5", with wipe/brush
27	46252	Suction Nozzle for Bucket, ABS plastic

* To order an antistatic (ESD) version, add E to the end of Part No.

Cleaning accessories Ø50 mm /2"




ERGO Grip for better ergonomy.
Fits on all Ø50 mm /2" suction pipes and Ø50 mm /2" bulk nozzle.


* To order an antistatic (ESD) version, add E to the end of Part No.

No	Part No	Description
1	7266	Aluminium wand
2	7267	Aluminium wand, with wear strip
3	7265	Chrome suction pipe Ø50 mm/ 2"
4	7268	Chrome steel extension wand, 710 mm/28"
	7269	Aluminium extension wand, 710 mm/28"
5	7033	Chrome steel hand pipe
6	7271	Chrome steel hand pipe, curved
7	7285	ERGO Grip handle
8	7272*	Tapered nozzle
9	7277*	Tapered nozzle
10	7212	Flat nozzle, L = 400 mm /15.7"
11	7295	Bulk nozzle
12	7013	Rubber floor tool
13	7281*	Floor nozzle W 200 mm /7.8"
14	7238*	Cast aluminium floor tool, 500 mm/19.6"
15	7307	Gulper floor tool, aluminium
16	7149	Chip nozzle 50x70x243 / 1.9"x2.7"x9.6"
17	7030	Suction nozzle
18	7279*	Suction brush
19	7016*	Suction nozzle with brush
20	7274	Rubber part for suction brush
21	7263	Brush for 7274, 7279
22	726301*	ESD brush for 7278, 7279
23	7398	Brush for 7278, 7279, hard, white

Cleaning accessories Ø76 mm /3"



Part No	Description
7126	Clamp for scraper
7127	Scraper for suction lance
7129	Handle, complete
7161	Bulk nozzle
7162	Suction lance



About Suction Hoses

Hoses need to have different characteristics depending on their intended use. Dustcontrol supplies hoses that are:

- wear-resistant, lightweight and flexible
- unaffected by extremes of temperature
- crushproof
- antistatic

When using long suction hoses that are coupled together, the hose closest to the suction casing should be the one with the smallest diameter and it should be no longer than 9,8 ft /3 m. Coupling should be carried out using external couplings that are easy to use.

Our selection of Suction Hoses

PRODUCT	Part No	Dimension Ø [mm/in]	Standard length [m/ft]	Colour	Material	Temp °F /°C max/min	Anti-static/ ESD	Abrasion resistance	UV and ozone resistance	Resistance to welding fumes	Resistance to solvent and oil	FDA
Suction hoses, standard	2001	76/3	10,15 /32,49	Blue	PE	140/–22/+60/–30	No	2	2	3	3	
	2401	50/2	5,10,15,20,25,30 /16,32,49,65,82,98	Blue	PE	140/–22/+60/–30	No	2	2	3	3	
	2111	38/1.5	5,10,15,20,25,30 /16,32,49,65,82,98	Blue	PE	140/–22/+60/–30	No	2	2	3	3	
	2112	32/1.25	5,10,15,20,25,30 /16,32,49,65,82,98	Blue	PE	140/–22/+60/–30	No	2	2	3	3	
	2113	25/1	5,10,15,20,25,30 /16,32,49,65,82,98	Blue	PE	140/–22/+60/–30	No	2	2	3	3	
Suction hoses, heat-resistant	2004	50/2	5,10,15 /16,32,49	Grey	PP(EPDM)	194/–40/+90/–40	No	3	2	1	4	
	2003	38/1.5	5, 10,15 /16,32,49	Grey	PP(EPDM)	194/–40/+90/–40	No	3	2	1	4	
Suction hoses, antistatic	2024*	76/3	5, 10,15 /16,32,49	Black	PE	140/–4/+60/–20	Yes	2	2	3	3	
	2013*	50/2	5,10,15,20 /16,32,49,65	Black	PE	140/–4/+60/–20	Yes	2	2	3	3	
	2012*	38/1.5	5,10,15,20 /16,32,49,65	Black	PE	140/–4/+60/–20	Yes	2	2	3	3	
	2005*	32/1.25	5,10,15,20 /16,32,49,65	Black	PE	140/–4/+60/–20	Yes	2	2	3	3	
	2025*	25/1	5,10,15,20 /16,32,49,65	Black	PE	140/–4/+60/–20	Yes	2	2	3	3	
Hose, ATEX	2027*	38/1.5	5,10,15,20 /16,32,49,65	Black	PE	140/–4/+60/–20	Yes	2	2	3	3	
	2028*	50/2	5,10,15,20 /16,32,49,65	Black	PE	140/–4/+60/–20	Yes	2	2	3	3	
Suction hoses, PU extra abrasion-resistant	2056	76/3	10/32	Transparent	PU	194/–40/+90/–40	Yes**	1	1	3	1	
	2054	50/2	10/32		PU	194/–40/+90/–40	Yes**	1	1	3	1	
	2055	38/1.5	10/32		PU	194/–40/+90/–40	Yes**	1	1	3	1	
Super D superelastic	2038	38/1.5	15/49	Black/white	PVC	185/–23/+85/–5	No	2	2	2	4	
	2039	50/2	15/49	Black/white	PVC	185/–23/+85/–5	No	2	2	2	4	
Suction hose	44140	38/1.5	10/32	Transparent	PU	-40 to +90		2	2	2	2	x
Suction hose	44141	50/2	10/32	Transparent	PU	-40 to +90		2	2	2	2	x
Suction hose	44142	76/3	10/32	Transparent	PU	-40 to +90		2	2	2	2	x

Resistance Scale


1 Excellent
2 Good
3 Limited
4 Poor

* To order an antistatic (ESD) version, add the letter E to the end of the Part No.

** The wire helix must be bared and left in contact with conductive material for static discharge.

Suction Hoses

Turnable Hose Connectors




Part No	Description
2114*	Connecting sleeve, turnable Ø1.5"/1,5" /38/38
2128*	Coupling sleeve, turnable Ø2"/1.5" /50/38
2129*	Coupling sleeve, turnable Ø2"/2" /50/50

Part No	Description
2131*	Intermediate sleeve, turnable Ø2"/1.5" /50/38
2132*	Connecting sleeve, turnable Ø1.2"/1.5" /32/38
2133*	Coupling sleeve, turnable Ø1.5"/1.2" /38/32
2171*	Coupling sleeve, turnable Ø1.2"/1.2 /32/32


*To order an antistatic (ESD) version, add E to the end of Part No.

Suction Hose Quick Coupler



Multi-Connection for Hand-held Power Tools with Integrated Suction Casings


The multi-connections fits onto suction casings with an outlet diameter of 0.98-1.37 inch /25-35 mm. Cut off a section at the required diameter (it is pre-marked with: 25, 27, 29, 31, 33, 35 mm) and slip the multi-connection over the tubing. Connection sleeves 2114 or 2115 then fit onto the other end to connect the hose.



Part No	Description
42497*	Multi-connection for hand-held power tools with integrated suction casings Ø25-35 mm
2175*	Threaded Multi-connection for hand-held power tools with integrated suction casings Ø25-35 mm
2114*	Coupling socket Ø1.5/1.5" 38/38 mm, turnable

Suction Hoses

Non-Turnable Hose Connectors



Part No	Description
2008*	Coupling socket Ø3"/2" /76/50
2014	Coupling socket Ø2.7"/2.7" /70/70
2100*	Intermediate sleeve Ø3"/2" /76/50
2101*	Intermediate sleeve Ø1.2"/0.98" /32/25
2106*	Connecting sleeve Ø0.67"/1.2" /17/32
2107*	Coupling socket Ø2"/2" /50/50
2108*	Coupling socket Ø2"/1.5" /50/38

Part No	Description
2115	Connecting sleeve Ø1.2"/1.2 /38/38
2116	Connecting sleeve Ø1.2"/1.2 /32/32
2118	Connecting sleeve Ø1.2"/1.2 /32/32
2120*	Intermediate sleeve Ø2"/1.5" /50/38
2121*	Intermediate sleeve Ø1.5"/1.2" /38/32
2156*	Coupling Nipple 75/72.5. 2156 is used to connect the 76 mm hose to flap valve, 76/76 art. 3237


Part No	Description
2167*	Connecting sleeve Ø0.98"/0.98" /25/25
2168*	Hose connector Ø1.2" /32
2169*	Hose connector Ø1.5" /38
2170*	Hose connector Ø2" /50




*To order an antistatic (ESD) version, add E to the end of Part No.

Camlock Retrofit Kit

Part No	Description
44585	CAMLOCK KIT 3" PP
44585-1	CAMLOCK KIT 3" AL
44585-2	CAMLOCK KIT 2" PP
44585-3	CAMLOCK KIT 2" AL
44585-4	CAMLOCK KIT 4" PP
44585-5	CAM LOCK KIT 4" AL






Accessories and Consumables

Hoses Sets

Part No

2125	Hose set Ø50/38 L = 7 m Ø2"/1.5" L = 23 ft
2126	Hose set Ø 50/38 L = 7 m Ø2"/1.5" L = 23 ft antistatic
2006	Hose set Ø 38 L = 2 m Ø1.5" L = 6.5 ft
2015	Hose set Ø38/1.5" L = 2 m/6,5ft
2105	Hose set Ø38/1.5" L = 5 m/16ft**

** Standard suction hose, turnable, non removable connector.(Replacement to standard hose kit)




Characteristics of Materials

DESCRIPTION	Dimension Ø [mm/in]	Part No	Colour	Material	Temp °F max/min/ Temp °C max/min	Antistatic	Abrasion resistance	UV and zone resistance	Resistance to welding fume	Resistance to solvent and oil
Coupling socket	76/50 /3/2	2008*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	50/50 /2/2	2107*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	50/38 /2/1.5	2108*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	76/50 /3/2 (PU)**	2161*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
Coupling socket	76/50 /3/2	2162*	Blue	NBR	248/-76/120/-60	Yes	2	3	3	2
Coupling sleeve	50/50 /2/2	2129*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	50/50 /2/2 (PU)**	2158*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	50/38 /2/1.5 (PU)**	2157*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	50/38 /2/1.5	2128*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	38/32 /1.5/1.25	2133*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	32/32 /1.25/1.25	2171*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
Connecting sleeve	32/38 /1.25/1.5	2132*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	38/38 /1.5/1.5 (PU)**	2159*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	38/38 /1.5/1.5	2114*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	50/50 /2/2	2129*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	25/25 /1/1	2167*	Black	TPE	284/-4/140/-20	Yes	1	2	3	1
	38/38 /1.5/1.5	2115*	Black	TPE	284/-4/140/-20	Yes	1	2	3	1
Connecting sleeve	26/38 /1/1.5	2109*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	26/32 /1/1.25	2110*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	17/32 /0.7/1.25	2106*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
Connecting sleeve	32/32 /1.25/1.25	2116	Grey	PE	45/-45	No	1	2	3	1
	25/25 /1/1	2117	Grey	PE	45/-45	No	1	2	3	1
Inter, sleeves	50/38 /2/1.5	2131*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
	50/38 /2/1.5 (PU)**	2160*	Black	PA12	284/-4/140/-20	Yes	1	2	3	1
Inter, sleeves	76/50 /3/2	2100*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	50/38 /2/1.5	2120*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	38/32 /1.5/1.25	2121*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
	32/25 /1.25/1	2101*	Black	EPDM	284/-76/140/-60	Yes	2	1	2	4
Hose connector	50/2	2403	Grey	PE	45/-45	No	2	2	3	3
	38/1.5	2118	Grey	PE	45/-45	No	2	2	3	3
	32/1.25	2119	Grey	PE	45/-45	No	2	2	3	3
Hose connector	50/2	2170*	Black	EPDM	284/-4/140/-20	Yes	1	2	3	1
	38/1.5	2169*	Black	EPDM	284/-4/140/-20	Yes	1	2	3	1
	32/1.25	2168*	Black	EPDM	284/-4/140/-20	Yes	1	2	3	1

* Antistatic is defined as having a conductivity of < 10^6 Ω
To order an antistatic ESD version, add the letter E to the end of the part No.
** The wire helix must be bared and left in contact with conductive material

Resistance Scale

1 Excellent
2 Good
3 Limited
4 Poor


H
G
F





Cleaning accessories Ø38 mm /1.5"







DC Reach – High Level Cleaning System

With our innovative cleaning technology DC Reach, it has never been easier to remove dust and combustible materials from high altitudes and hard-to-reach places. Traditionally, cleaning at height has involved hydraulic lifting aids, work platforms and at least two people to carry out the job safely. Now the task can be solved safely by one person.

The system consists of a pipe system with straight pipe parts and bends that are connected as desired. Along with this, there are several suction nozzles to meet the customer's unique needs.

In addition to the standard version of DC Reach, there is also DC Reach ATEX for customers who need equipment suitable for an ATEX environment. All these components are certified and meet the Atex-directive 2014/34/EU: ISO 80079-36:2016, ISO 80079-37 and are NFPA certified.

Part No	DC Reach System
7600	DC Reach Standard
7620	DC Reach ATEX

Standard Set

7601	Pipe, Carbon fiber, L -1.25m x Ø38mm
7602	Bend 135 degrees
7603	Bend 90 degrees
7604	Bend 45 degrees
7605	Adaptor for Nozzle
7606	Adaptor for Hose
7607	Nozzle, W200mm
7608	Nozzle, W380mm
7609	Floor Nozzle, W300mm
7611	Bag for Pipes
7613	Bag for Accessories
7615	Nozzle, round
7616	Nozzle, elonged, W200

DC Reach Standard Set Prod No 7600



ATEX Set

7621	6 x ATEX Pipes, Carbon fiber, L - 1.25m x Ø38mm
7622	ATEX Floor Nozzle, W200mm
7623	ATEX Flat Nozzle
7624	ATEX Nozzle, W200mm
7626	ATEX Adaptor for Hose
7627	ATEX Bend 135 degrees
7628	ATEX Bend 90 degrees
7629	ATEX Bend 45 degrees
7630	ATEX Nozzle, straight
7611	Bag for Pipes
7613	Bag for Accessories

DC Reach ATEX Set Prod No 7620



Suction Casings





Finding the right suction casing


Machine		Make			Type	
D	d	H	h	A	B	M

Legend


F	Fibre disc
D	Diamond cup grinding disc
N	Depressed centre disc
K	Abrasive disc, diamond disc
S	Abrasive cup stone

If you cannot find the suction casing you are looking for, contact your sales representative for pricing information regarding a product tailored to your specific needs.


F
Fibre Disc




D
Diamond Cup Grinding Disc



N, K
Depressed Centre Disc, Abrasive Disc, Diamond Disc



S
Abrasive Cup Stone



Suction Casings Suction Casing Kit for Fibre Discs (F)


1

Measure the diameter of the disc.



2

Measure the diameter of the mounting collar on the machine - ØD and the height of the machine - H.



3



Check out our range of Suction Cases to fit your need. Mount the Suction Casing and ready to use!

Technical data

DISC DIAMETER	Ø D [mm/in]	H [mm/in]	Connection, Ø [mm/in]	Part No
1½–3" (38–75 mm)	27 /1.1	*	32 /1.25	6833*
4" (100 mm)	40–49 /1.6–1.9	39–44 /1.5–1.7	32 /1.25	6670
4½" (115 mm)	40–49 /1.6–1.9	39–48 /1.5–1.9	32 /1.25	6671
5" (125 mm)	40–49 /1.6–1.9	39–48 /1.5–1.9	32 /1.25	6672
5" (125 mm)	50/2	38–61 /1.5–2.1	32 /1.25	6673
7" (175 mm)	54–61 /2.1–2.4	50–59 /2–2.3	38 /1.5	6674

** Some Hitachi machines have a Ø40 mm /1.6" conical neck. With these, it is necessary to buy an aluminium ring (Part No. 6270). When fitted on the machine, this aluminium ring enlarges the ØD of the machine to 50 mm /1.9" – therefore choose the 5" N, K suction casing kit – Part No. 6678.



Suction Casings Suction Casing Kit for Diamond Cup Grinding Discs (D)


1

Measure the diameter of the disc.



2

Measure the diameter of the mounting collar on the machine - ØD and the height of the machine - H.



3



Check out our range of Suction Cases to fit your need. Mount the Suction Casing and ready to use!

Technical data

DISC DIAMETER	Ø D [mm/in]	H [mm/in]	Connection, Ø [mm/in]	Part No
4½" (115 mm)	40–49 /1.6–1.9	49–54 /1.9–2.1	32 /1.25	6681
5" (125 mm)	40–49 /1.6–1.9	49–70 /1.9–2.8	32 /1.25	6682
5" (125 mm)	50/2	38–61 /1.5–2.4	32 /1.25	6673
7" (175 mm)	54–61 /2.1–2.4	63–72 /2.5–2.8	38 /1.5	6683
7" (175 mm)	62–65 & 74–77 /2.4–2.6 & 2.9–3	63–86 /2.5–3.4	38 /1.5	6684



Suction Casings

Suction Casing Kit for Depressed Centre Discs, Abrasive Discs and Diamond Discs (N, K)

1


Measure the diameter of the disc.



Note: Max. thickness of disc = 18 mm.


2

Measure the diameter of the mounting collar on the machine ØD and the height of the machine - H.



3

Check out our range of Suction Cases to fit your need. Mount the Suction Casing and ready to use!




Technical data

DISC DIAMETER	Ø D [mm/in]	H [mm/in]	Connection, Ø [mm/in]	Part No
4 ½" (115 mm)	40–49 /1.6–1.9	31–46 /1.2–1.8	32 /1.25	6676
5" (125 mm)	40–45 /1.6–1.8	31–46 /1.2–1.8	32 /1.25	6677**
5" (125 mm)	46–53 /1.8–2.1	31–46 /1.2–1.8	32 /1.25	6678
9"*	112 /4.4	37 /1.5	38 /1.5	6221*
9"	68 /2.7	51 /2	38 /1.5	6202*
9"	74 /2.9	54 /2.1	38 /1.5	6302*
9"	74 /2.9	37 /1.5	38 /1.5	6349*
9"	50 /2	47 /1.9	38 /1.5	6500*
9"	62 /2.4	54 /2.1	38 /1.5	6416*
9"	62 /2.4	50 /2	38 /1.5	6438*
9"	62 /2.4	48 /1.9	38 /1.5	6555*
9"	65 /2.6	40 /1.6	38 /1.5	6842*
9"	64 /2.5	52 /2	38 /1.5	6427*
9"	58 /2.3	54 /2.1	38 /1.5	6537*
9" Georges Renault KL 365		59 /2.3	38 /1.5	6388*

* With the clamping rings welded on the suction casings.
** Some Hitachi machines have a Ø40 mm conical neck. With these, it is necessary to buy an aluminium ring (part no 6270). When fitted on the machine, this aluminium ring enlarges the ØD of the machine to 50 mm – therefore choose the 5" N, K suction casing kit – Part No 6678.

Connection Ø



Suction Casings

Suction Casing for Hammer Drills, Chisels and Breakers







Suction casings B, H, M, L






No	Part No	Connection tool Ø [mm/in]	Hose connection Ø [mm/in]	Height [mm/in]
1	6621	48 /1.89	38 /1.5	158 /6.22
2	6622	43 /1.69	38 /1.5	158 /6.22
3	6077	32 /1.26	32 /1.26	112 /4.4
4	6078	61 /2.4	38 /1.5	178 /7
5	6001 (handpipe)	-	50 /2	100 /3.9
6	6130	Bellow for 6078, 6621 and 6622		

Part No 6622 and 6077 are suitable for small chisel hammers.

Model-specific suction casings

Part No	Model	Hose connection Ø [mm/in]
6229	Atlas Copco RRD 37/RRD 57	38 /1.5
6152	Atlas Copco BBD 11/RRC 73	38 /1.5

Suction Casings Spare Parts for Suction Casings

	Description		Dimension D1 [mm/in]	D2 [mm/in]	H [mm/in]	Part No
	Plastic ring for saucer grinder	5 S 6 S	121 /4.8 147 /5.8	139 /5.5 164 /6.5	50 /2 50 /2	6003 6004
	Rubber collar for fibre disc (F)	1 ½ F 2 F 3 F 4 F 4 ½ F 4 ½ F 5 F	39 /1.5 39 /1.5 39 /1.5 72 /2.8 72 /2.8 72 /2.8 72 /2.8	59 /2.3 69 /2.7 95 /3.7 117 /4.6 135 /5.3 135 /5.3 145 /5.7	23 /0.9 23 /0.9 25 /1 13 /0.5 13 /0.5 23 /0.9 13 /0.5	6314 6313 6312 6182 6181 618100 6195
	Rubber collar for fibre disc (F)	5 F	96 /3.8	150 /5.9	15 /0.6	6006
	Rubber collar for oscillating. sanding machine	5 O 6 O	72 /2.8 96 /3.8	145 /5.7 170 /6.7	38 /1.5 28 /1.1	6212 6180
	Rubber collar for fibre disc (F)	7 F 7 F 8 F 9 F	112 /4.4 112 /4.4 112 /4.4 113 /4.5	196 /7.7 196 /7.7 221 /8.7 250 /10	19 /7 35 /1.4 41 /1.6 32 /1.25	6002 6034 6211 6039

Suction Casings DC Dust Shroud Kit

Suction Casing Kit for most Angle Grinders

We are launching a new series of suction casings - DC Dust Shroud. The suction casings can be mounted on the most common angle grinders such as Makita, Hitachi, Bosch M14, Dewalt, Metabo, Flex and Milwaukee and are the perfect tool for floor sanding carried out by hand.

The DC Dust Shroud includes spacers and collars to fit the different tool brands and is available in sizes D 125 mm and 175 mm. In addition, the dust shrouds are available in either aluminum or composite design.

Features:

- The DC Dust Shroud includes spacers and collars. (4)
- The built-in air valve can be adjusted to reduce the vacuum pressure if the suction of the dust extractor is too strong. (3)
- Replaceable nylon strips (5 mm) are included, extending the life of the Dust Shroud. (1)
- The Dust Shroud has a flip front that allows 90-degree edge grinding. (6)


Part No DC 2900L

46332	Expert DC Dust Shroud 125 mm
46333	Expert DC Dust Shroud 175 mm
46334	PRO DC Dust Shroud 125 mm
46335	PRO DC Dust Shroud 175 mm
46343	Expert DC Dust Shroud US 5"
46344	Expert DC Dust Shroud US 7"
46345	PRO DC Dust Shroud US 5"
46346	PRO DC Dust Shroud US 7"



Suction Casings DC Dust Shroud Kit

Suction Casing Kit for most Angle Grinders



1	Replaceable nylon wear strip
2/7	Multitfit vacuum nozzle port
3	Adjustable air flow control
4	Various collars available to suit most angle grinders
5	Rubber diaphragm for self-levelling height adjustment
6	Flip top front for edge grinding



Part no 2115
Connecting Sleeve 38/38 Antistatic



Part no 46347
DELUX SPANNER

				**Part no 46332** Expert DC Dust Shroud 125 mm **Part no 46343** Expert DC Dust Shroud US 5"
				**Part no 46333** Expert DC Dust Shroud 175 mm **Part no 46344** Expert DC Dust Shroud US 7"
				**Part no 46334** PRO DC Dust Shroud 125 mm **Part no 46345** PRO DC Dust Shroud US 5"
				**Part no 46335** PRO DC Dust Shroud 175 mm **Part no 46346** PRO DC Dust Shroud US 7"

Dustlight



Technical Data

Dimensions (HxWxD)	69x69x33 [mm]
Weight	150 [g]
Battery Runtime	Up to 20 hours (Eco up to 40 hours)
Particle Sizes	Respirable, PM1, PM2.5, PM10
Sensory Technology	Photometric
Charging Port	USB

Dustlight is available in the following areas:

Part No	Description
46866	Dustlight Mini, EU, Norway Switzerland
46995	Dustlight Mini, USA

Dustlight Productpage:

Accessories of Dustlight



Main Article	Description
46866	Dustlight Mini, EU, Switzerland, Norway
46995	Dustlight Mini, USA
Accessories	**Description**
46867	Click Fast - Chest Strap 1
46868	Click Fast - Bracelet 2
46869	Click Fast - Clothing Fastening 3
46870	Click Fast - Leather Loop for Belt 4
46871	Click - Fast Click 5
46872	USB Charger / Power Supply Unit 6
46873	Magnetic Charging Cable 7
46874	Dustlight Box for 6 pcs 8
46875	Dustlight Box for 2 pcs 9

8 + 9 Storage boxes for 6 or 2 Dustlight(s), 6 or 2 x USB charging cable(s), power supply unit and distributor with 6 or 2 USB ports.



Dustlight – Your best Companion for Any Industry out there



Knowledge of the exact level of dust concentrations is vital for a secure assessment. And by continious monitoring and recording of the data you will prevent dangerous particles in the air.

Dustlight is Handy, in Pocketsize

Dustlight is a handheld particle monitor developed for use in trade and industry. It measures respirable dust and is set on silica dust as default. PM10 particles of inhalable dust, as well as PM1 and PM2.5. Dustlight has illuminated areas that change color when critical values are exceeded, based on the TRGS 900 limit values for respirable dust.

The colors shift from yellow to red if the dust level exceeds 1250 µg/m³ (can be altered due to the country or a specific regulation stored by using the App), while the transition from green to yellow can be adjusted via an app, with the default setting at 10% of the limit value.



The device has a display showing both current and average measurements and stores data to visualize trends over time.

Monitor and Share your results by the Dustlight App

Dustlight App

Connect the device to the app and get clear visualization and analysis of stored data.

3 Software plans available – Scan the QR code for more info!

BASIC (Included)	BUSINESS	CORPORATE
Max 2 Devices	Max 15 Devices	Unlimited Devices

Dust Protection Door



The Dust Protection Door is designed to ensure a clean and safe work environment during renovation, demolition, or other construction activities where dust spread can pose a problem. By effectively isolating the work area, the risk of dust spreading to surrounding spaces is minimized.

Combine with DC AirCube for maximum effect.
Together with DC AirCube (model 1200/2000), negative pressure and controlled airflow direction are created – keeping the dust in place and the environment healthy.

Easy installation and universal fit.
Fits all door sizes. Installs without special tools and can be easily disassembled when the job is done.

Multiple options – based on your needs.
Choose between two complete kits or a standalone door – customize according to the project's needs.

Dust Protection Door
(Part No 46352)

Supplied With:
Transport Bag (Part No 46353)
Protecting Adhesive Tape 50mm x 50m (Part No 46356)
Special Adhesive Tape 19mm x 25m (Part No 463576)

Technical Info

Dimensions HxW [mm/in]	1950x650 / 77x26
Weight [kg/lb]	9.5 / 21
Door Opening [mm/in]	580 / 23

Plesae note that the air cleaners are not included in the kits below.



Dust Protection Door Kit Ø200
(Part No 44464)
Suitable for DC AirCube 600

Supplied With:
Dust Protection Door Ø300/250 mm (46352)
Hose Clamp (4464)
Ventilation Hose Ø200 (2422)
Transport Container Ø250 (46367)



Dust Protection Door Kit Ø250
(Part No 46907)
Suitable for DC AirCube 1200

Supplied With:
Dust Protection Door (Part No 46352)
Hose Clamp (Part No 3352)
Ventilation Hose Ø250 (Part No 2182)
Transport Container for vent. hose Ø250 (Part No 46367)



Dust Protection Door Kit Ø330
(Part No 46908)
Suitable for DC AirCube 2000

Supplied With:
Dust Protection Door (Part No 46352)
Hose Clamp (Part No 3352)
Ventilation Hose Ø330 (Part No 2176)
Transpost Container for vent. hose Ø330 (Part No 46368)

Spareparts & Accessoriess



Sparepart Set (46354)



Reducing Ring Ø250/300 (46355)



One-hand Ceiling Support (46358)



Adhesive Sealing (46359)



Select the right bag for your machine.

46145



42702



42384



43619



42111



42951




42285



42190



42291



4714



4314





4712 D

Bulk Bag
– Discharge Option for
Stationary Vacuum Systems

44077 D 25 m /82 ft



432177 B 23 m /75 ft



45379 E XXX-Strong 20 m /65 ft



44763 A 8 m /26 ft



Plastic Bags

MODEL	Standard Bag [Prod No]	Antistatic/ESD Bag [Prod No]	Volume Standard Bag [l/gal]	Size Standard Bag WxH [mm/in]
DC 1800	42291 [A]	42951 [D]	30/7.9	350x200x550 /13.8x7.9x21.7
DC 1800 XL	42285 [D]	42384 [D]	70/15.4	360x700 /14x27.5
DC 2900 c	42702 [A]	-	30/7.9	280x180x800 / 11x7.1x31.5x34.2 + 23 m /75 ft
DC 2900 L	44763 [A] + 432177 [B] Longopac	-	20/5	8 m /26 ft + 23 m /75 ft
DC 1800 H Asbestos a	42285 [D]	42384 [D]	20/5	360x700 /14x27.5
DC 2900 H Asbestos a	42285 [D]	42384 [D]	70/15.4	360x700 /14x27.5
DC Tromb 400 c	43619 [A]	42384 [D]	33/8.7	500x850 /19.7x33.5
DC Tromb 400 a	42285 [G]	42384 [D]	70/15.4	360x700 /14x27.5
DC Tromb 400 L	432177 [B] Longopac	-	-	23 m /75 ft
DC Tromb Turbo Direct c	43619 [A]	42384 [D]	33/8.7	280x170x870 /11x6.7x34.3
DC Tromb Turbo Direct L	432177 [B] Longopac	-	-	23 m /75 ft
DC Tromb Turbo VFD c	43619 [A]	42384 [D]	33/8.7	280x170x870 /11x6.7x34.3
DC Tromb Turbo VFD L	432177 [B] Longopac	-	-	23 m /75 ft
DC Tromb Twin aa	42285 [G]	42384 [D]	70/15.4	360x700 /14x27.5
DC Tromb Twin cc	43619 [A]	42384 [D]	33/8.7	280x170x870 /11x6.7x34.3
DC Tromb Twin cL	43619 [A] + 432177 [B] Longopac	42384 [D]	33/8.7	280x170x870 /11x6.7x34.3 + 23 m /75 ft
DC Tromb Twin LL	432177 [B] Longopac	-	-	23 m /75 ft
DC Tromb 400 H Asbestos	42285 [G]	42384 [D]	70/15.4	360x700 /14x27.5
DC Chip Extractor	4714 [C]	-	100/26.4	700x1100 /27.5x43.3
DC 4000 PCB	42285 [D]	42384 [D]	70/15.4	360x700 /14x27.5
DC 5900 c	46145 [A]	-	60/15.9	420x220x1000 /16.5x8.7x39.4
DC 5900 L	44077 [D] Longopac + 44248 [E]	-	-	25 m /82 ft
DC 5900 H Asbestos	46141 [D]		75/19.8	700x1100 /27.5x43.3
DC Storm c	46145 [A]	-	60/15.5	640x1000 /25.2x39.4
S 11000	4714 [C]	42111 [C]	100/26.4	700x1100 /27.5x43.3
S 11000	44077 [D] Longopac + 46828 [E]	42111 [C]	90/23	25 m /82 ft / 700x1100
S 2100/32000/34000/34000X	4714 [C]	42111 [C]	100/26.4	700x1100 /27.5x43.3
DC 50W /DC 75W	42190 [D]	-	-	-
DCF Storm c	46145 [A]	-	60/15.5	640x1000 /25.2x39.4
DCF Storm L	44077 [D] Longopac	-	-	25 m /82 ft
DCF 2900 c	42702 [A]	-	30/7.9	440x550 /17x 21.7
DCF 2900 L	44763 [A]	-	-	8 m /26 ft
DCF Tromb c / DCF Tromb a	43619 [A] / 42285 [G]	-	33/8.7 / 70/15.4	280x170x870 /11x6.7x34.3
DCF Tromb L	432177 [B] Longopac	-	-	23 m /75 ft
DCF Mobile	4714 [C]	42111 [C]	100/26.4	700x1100 /27.5x43.3
F 20000	4714 [C]	42111 [C]	100/26.4	700x1100 /27.5x43.3
F 30000	4714 [C]	42111 [C]	100/26.4	700x1100 /27.5x43.3
DC 1800/2800 EX	-	42951 [F]	40/8.8	360x400 /14x15.7
DC Tromb Turbo EX	-	42385 [G]	175/38.5	360x700 /14x27.5
DC 5800 Turbo EX	-	42111 [C]	175/38.5	450x1100 /17.7x43.3
DC 1800 TR EX	-	42384 [F]	70/15.4	360x700 /14x27.5
DC 2800 TR EX	42285 [D]	42384 [D]	70/15.4	360x700 /14x27.5
DC Tromb TR EX	-	42384 [F]	70/15.4	360x700 /14x27.5
DC 5900 Turbo TR	46145 [A]	-	60/15.5	640x1000 /25.2x39.4


A Set of 10 bags
B Set of 4 bags
C Set of 50 bags
D Individual bags
E Adaption Kit for Longopac / Holder for Longopac Midi
F Set of 25 bags
G Set of 5 bags



Bag strap (Part No)
4313, 1 m **4613**,1.5 m

Choose the Right Filter

Pleated design increases the filtering surface. For filtering to be effective without affecting user performance, the air velocity through the filter must be maintained but without overloading the volume capacity of the filter media. Suitable filter loadings vary with the material being extracted. Suitable filter loading, measured in m^3/hr per m^2 of filter area, for concrete dust is for example, a maximum of 120m^3/hr per m^2, while welding fume is only 60m^3/hr per m^2 as it exerts a higher filter loading or simply put, it will block the filters more quickly. This is always considered in Dustcontrol's design criteria.



Our dust extractor separates dust in three stages:

1. Large particles are separated dynamically in the **Cyclone**.
2. Filtration then takes place in the pleated **Fine Filter**.
3. Followed by a pleated **Microfilter** HEPA H13.

The Fine Filter. This filter is designed to capture the small particles that are not captured in the pre-separator or cyclone.




Cellulose Fine Filter
A high-quality, standard filter with high filtration efficiency. Epoxy-treated for improved resistance to humidity and other elements. It is pleated around a support cylinder.

Polyester Fine Filter
A high-quality filter resistant to most substances. Perfect for use in wet environments such as mechanical workshops in which cutting fluids etc. is used. Slightly smoother surface than the cellulose filter, enabling more efficient cleaning and a longer service life.

PTFE Fine Filter
The polyester filter is treated with PTFE, meaning that the filter coating can easily be separated from the surface. This type of filter is suitable for use in applications such as floor grinding.

A Pre-Filter is a basic filter used with air cleaners in order to capture large particles and relieve the loading on the HEPA filter. The pre-filter is designed as a pleated filter in casette or textile form. It is disposable. Each Pre-Filter filter is individually tested for level G4 compliance.






Conical pleated filter with sealing flange and protective jacket.
The separate HEPA filter is fitted inside the fine filter.



Air cleaner



Our Air cleaners separate dust in two stages:

4. Large particles are separated by the **Carpet Pre-filter,** or a
5. **Pre-filter cartridge,**
6. followed by a pleated **HEPA H13 Microfilter**

However we also have a number of filters in class H14 for our standard solutions to be ordered separately.

Microfilter, HEPA filter, Absolute Filter goes by many names, and has a filtration efficiency of 99.995%.

PLEASE NOTE! We are now introducing HEPA H14 filers as an additional part no for our air cleaners and some of or dust extractors.
Go to page 38-39 for more info



A HEPA Filter
The HEPA filter is assembled from a very fine-meshed fibreglass textile with extremely deep-acting properties. One or two layers of e.g. cellulose may be added to improve rigidity.

Each HEPA filter is individually tested for level H13 compliance. The test report can be obtained on request.

Dustonctrol´s HEPA filters comply with the requirements for H-class dust extractors. The HEPA filter should be replaced when it becomes saturated.

All Dustcontrol´s dust extractors and air cleaners, have a separate HEPA H13 filter installed after the fine filter or pre-filter. The filter systems in all Dustcontrol dust extractors are built to comply with the the stringent IEC machine classification H.



Filters

DC **AirCube**

Part No	Type of filter / Machine	Construction	Material	Area [m²/ft²]	Classification	Max temp
46395	**Pre-filter,** AirCube 600	Pleated carpet	Polyester	0.71 /7.64	G4	176°F /80°C
46378	**HEPA filter,** AirCube 600	Pleated	Cellulose, fibreglass	4.47/48.1	HEPA H13 EN 1822-1	176°F /80°C
42918	**Pre-filter,** AirCube 1200	Cartridge	Polyester	0.4 /4.3	G4	140°F /60°C
42940	**HEPA filter,** AirCube 1200	Pleated	Cellulose, fibreglass	5 /54	HEPA H13 EN 1822-1	194°F /90°C
42917	**Pre-filter,** AirCube 2000	Cartridge	Polyester	0.5 /5.4	G4	140°F /60°C
42896	**HEPA filter,** AirCube 2000	Pleated around support cylinder	Cellulose, fibreglass	10 /107	HEPA H13 EN 1822-1	194°F /90°C
46416	Pre-Filter with Activated Carbon Layer, AirCube 1200	Cartridge	Polyester	0.42 /4.52	Carbon G4/ Activated Carbon	176°F /80°C
46417	Pre-Filter with Activated Carbon Layer, AirCube 2000	Cartridge	Polyester	0.58 /6.24	Carbon G4/ Activated Carbon	122°F /50°C

HEPA H14 EN 1822-1

DC **1800/2900,** DC **1800/2800 EX,** DC **1800/2800 TR EX,** DC **1800/2900 Asbestos**

Part No	Type of filter / Machine	Construction	Material	Area [m²/ft²]	Classification	Max temp
42029	**Fine filter,** DC 1800/2900cL	Pleated around support cylinder	Cellulose, epoxy-treated	1.5 /16.2	IEC EN 60335-2-69 Part 1	176°F /80°C
42029ST	**Fine filter x 48**	Pleated around support cylinder	Celloluse	1.5 /16.2	IEC EN 60335-2-69 Part 1	176°F /80°C
42028	**Fine filter,** DC 1800/2900a, DC 1800/2900 Asbestos	Pleated	Polyester	1.5 /16.2	IEC EN 60335-2-69 Part 1	266°F /130°C
42028-01	**Fine filter,** DC 1800/2900, 1800/2800 TR EX DC 1800/2800 EX	Pleated	Polyester, antistatic	1.5 /16.2	IEC EN 60335-2-69 Part 1	266°F /130°C
42028-02	**Fine filter, PTFE** DC 1800/2900	Pleated	Polyester, PTFE	1.5 /16.2	IEC EN 60335-2-69 Del1	100 °C
42027	**HEPA filter,** DC 1800/2900, DC 1800/2800 EX, DC 1800/2800 TR EX, DC 1800/2900 Asbestos	Pleated	Cellulose, fibreglass	0.85 /9.1	HEPA H13 EN 1822-1	176°F /80°C
42926	**HEPA filter,** DC 1800 EX, H14	Pleated	Cellulose, fibreglass	0.85 /9.1	HEPA H14 EN 1822-1	176°F /80°C

DC **Tromb,** DC **Tromb Twin,** DC **Tromb Turbo,** DC **Tromb Turbo Twin,** DC **Tromb Turbo EX,** DC **Tromb Asbestos,** DC **Tromb Turbo VFD Asbestos,** DC **Chip Extractor,** DC **Tromb Stationary, DC Tromb TR EX**

Part No	Type of filter / Machine	Construction	Material	Area [m²/ft²]	Classification	Max temp
44017	**Fine filter,** DC Tromb/Turbo/Twin, DC Turbo E, DC Tromb Turbo VFD Asbestos, DC Chip Extractor, Tromb Stat.	Pleated around support cylinder	Polyester	1.85 /20	IEC EN 60335-2-69 Part 1	176°F/80°C
44017-1	**Fine filter,** DC Tromb Turbo/TR EX	See above	Polyester, antistatic	1.85 /20	IEC EN 60335-2-69 Part 1	176°F/80°C
44043	**Fine filter**	Pleated around support cylinder	Cellulose, epoxy-treated	1.85 /20	IEC EN 60335-2-69 Part 1	176°F/80°C
44213	**Fine filter, PTFE**	Pleated around support cylinder	Polyester, PTFE	2.5 /30	IEC EN 60335-2-69 Part 1	266°F /130°C
44016	**HEPA filter,** DC Tromb/Turbo/Twin, DCTromb Turbo/TR EX, DC Tromb Turbo VFD Asbestos, DC Chip Extractor	Pleated	Cellulose, fibreglass	2.2 /23.7	HEPA H13 EN 1822-1	176°F/80°C
44016-1	**HEPA filter,** DC Tromb 600	Pleated	Cellulose, fibreglass	3.3 /35.6	HEPA H13 EN 1822-1	176°F/80°C
44017-2	**Fine filter,** DC Tromb 600	Pleated around support cylinder	Polyester	2.8 /30.2	IEC EN 60335-2-69 Part 1	176°F/80°C

DC **Tromb TR EX,** DC **4000 PCB**

Part No	Type of filter / Machine	Construction	Material	Area [m²/ft²]	Classification	Max temp
42025	**Fine filter,** DC 4000 PCB	Pleated	Polyester	1.8 /19.4	IEC EN 60335-2-69 Part 1	266°F /130°C
42025ST	**Fine filter x 24**	Pleated	Polyester	1.8 /19.4	IEC EN 60335-2-69 Part 1	266°F /130°C
4202501	**Fine filter,** DC Tromb TR EX	Pleated	Polyester, antistatic	1.5 /16.2	IEC EN 60335-2-69 Part 1	176°F /80°C
42024	**HEPA filter,** DC Tromb TR EX, DC 4000 PCB	Pleated	Cellulose, fibreglass	1.5 /16.2	HEPA H13 EN 1822-1	266°F /130°C

DC **5800 Turbo Ex,** DC **5900,** DC **5900 Asbestos,** DC **5900 TR,** DC **Storm 500/600/700**

Part No	Type of filter / Machine	Construction	Material	Area [m²/ft²]	Classification	Max temp
429203	**Fine filter, PTFE,** DC 5900	Pleated around support cylinder	Polyester, PTFE	5.0 /53.8	IEC EN 60335-2-69 Part 1	266°F /130°C
44081	**Fine filter, PTFE,** DC Storm 600/700L	Pleated around support cylinder	Polyester, PTFE	5.0 /53.8	IEC EN 60335-2-69 Part 1	266°F /130°C
429204	**Fine filter,** DC 5900c 9.2 kW S, DC 5900 Asbestos 4 kW, DC 5900 TR	Pleated around support cylinder	Polyester	5.0 /53.8	IEC EN 60335-2-69 Part 1	266°F /130°C
44212	**Fine filter,** DC Storm 500acL, DC Storm 600/700ac	Pleated around support cylinder	Polyester	5.0 /53.8	IEC EN 60335-2-69 Part 1	266°F /130°C
4292	**Fine filter,** DC 5900c 9.2 kW P, DC 5900c Asbestos 9.2 kW P	Pleated around support cylinder	Polyester	8.4 /90.4	IEC EN 60335-2-69 Part 1	266°F /130°C
429206	**Fine filter,** DC 5800 Turbo Ex	Pleated around support cylinder	Polyester	8.4 /90.4	IEC EN 60335-2-69 Part 1	266°F /130°C
42869	**HEPA filter,** DC 5800 Turbo Ex, DC 5900 4/9.2 kW S, DC 5900 Asbestos 4 kW (installed under top cover), DC 5900 TR, DC Storm 500acL	Pleated around support cylinder	Cellulose, fibreglass	2.7 /29	HEPA H13 EN 1822-1	176°F /80°C
42807	**HEPA filter,** DC Storm 600L, DC 5900c 9.2 kW S/P, DC 5900c Asbestos 9.2 kW P	Pleated around support cylinder	Cellulose, fibreglass	3.7 /39.8	HEPA H13 EN 1822-1	176°F /80°C



Filters for old models

DC **2500i**, DC **2500**, DC **2500 Twin**

Part No	Description	Construction	Material	Area [m²/ft²]	Classification	Max temp
4889	Fine filter	Pleated	Polyester	1.4 /15	IEC EN 60335-2-69 Part 1	266°F /130°C
404901	Fine filter	Pleated around support cylinder	Cellulose	1.5 /16.2	IEC EN 60335-2-69 Part 1	158°F /70°C
4821	HEPA filter K	Pleated	Cellulose, fibreglass	1.5 /16.2	HEPA H13 EN 1822-1	158°F /70°C
4133	HEPA filter (fitted in the fine filter)	Pleated around support cylinder	Cellulose, fibreglass	0.5 /5.4	HEPA H13 EN 1822-1	176°F/80°C

DC **2700c**, DC **2700i**, DC **2800c**, DC **2800c Rental**

(Machines from serial number 2527595 can be equipped with HEPA filter (Part No 42027).
Older models should be equipped with a HEPA combi-filter.

Part No	Description	Construction	Material	Area [m²/ft²]	Classification	Max temp
4889	Fine filter	Pleated	Polyester	1.4 /15	IEC EN 60335-2-69 Part 1	266°F /130°C
404901	Fine filter	Pleated around support cylinder	Cellulose	1.5 /16.2	IEC EN 60335-2-69 Part 1	158°F /70°C
4821	HEPA filter K	Pleated	Cellulose, fibreglass	1.5 /16.2	HEPA H13 EN 1822-1	158°F /70°C
4133	HEPA filter (fitted in the fine filter)	Pleated around support cylinder	Cellulose, fibreglass	0.5 /5.4	HEPA H13 EN 1822-1	176°F/80°C
40479	Combi-filter (Fine filter + HEPA filter), (GS Asbestos)	Pleated	Cellulose, epoxy-treated	1.5 /16.2	HEPA H13 EN 1822-1	176°F /80°C

Filters for old models

DC **3500**, DC **3500TR**, DC **3500 Stationary**, DC **5500**, DC **5500i**

Part No	Description	Construction	Material	Area [m²/ft²]	Classification	Max temp
408801	Fine filter	Pleated	Polyester	1.6 /17	IEC EN 60335-2-69 Part 1	176°F/80°C
408803	Fine filter	Pleated	Cellulose	1.6 /17	IEC EN 60335-2-69 Part 1	176°F/80°C
4821	HEPA filter, DC 3500 TR	Pleated	Cellulose, fibreglass	1.5 /16.2	HEPA H13 EN 1822-1	158°F /70°C
4366	HEPA filter, DC 3500 (installed on exhaust)	Pleated around support cylinder	Cellulose, fibreglass	1.2 /12.9	HEPA H13 EN 1822-1	176°F/80°C
4422	HEPA filter, DC 5500 5 kW, 9.2 kW S (installed under top cover)	Pleated around support cylinder	Cellulose, fibreglass	2.5 /26.9	HEPA H13 EN 1822-1	176°F/80°C
4017	HEPA filter, DC 5500 9.2 kW P (installed on exhaust)	Pleated around support cylinder	Cellulose, fibreglass	2.8 /30	HEPA H13 EN 1822-1	176°F/80°C

DC **3500i**, DC **5700c**, DC **5800 a/c 5 kW**, DC **5800 a/c PTFE;** DC **Storm LPG**

Part No	Description	Construction	Material	Area [m²/ft²]	Classification	Max temp
4917	Combi-filter DC 3500i (Fine filter + HEPA H13 filter)	Pleated	Cellulose, fibreglass	1.5 /16.2	HEPA H13 EN 1822-1	176°F/80°C
4422	HEPA filter, DC 5700 5 kW, 9.2 kW S (installed under top cover)	Pleated around support cylinder	Cellulose, fibreglass	2.5 /26.9	HEPA H13 EN 1822-1	176°F/80°C
4017	HEPA filter, DC 5700 9.2 kW P (installed on exhaust)	Pleated around support cylinder	Cellulose, fibreglass	2.8 /30	HEPA H13 EN 1822-1	176°F/80°C
42807	HEPA filter, DC Storm LPG,	Pleated around support cylinder	Cellulose, fibreglass	3.7 /39.8	HEPA H13 EN 1822-1	176°F /80°C

DC **380**, DC **1500,** DC **AirCube**

Part No	Description	Construction	Material	Area [m²/ft²]	Classification	Max temp
42690	Pre-filter, AirCube 500	Pleated carpet	Polyester	0.18 /1.9	G4	176°F /80°C
42692	HEPA filter, AirCube 500	Pleated	Cellulose, fibreglass	4.56/49	HEPA H13 EN 1822-1	176°F /80°C
42136	HEPA filter, DC AirCube	Pleated HEPA filter box	Fibreglass	5.2 /55.9	EN 1822-1, HEPA H13	176°F/80°C

DC **3700c**, DC **3800a/c**, DC **3800c Turbo**, DC **3800 Turbo EX**, DC **3800c Twin** DC **3800 TR S**, DC **3800i**, DC **3800 Stationary,** DC **3900,** DC **Wood Shavings Extractor**

Part No	Description	Construction	Material	Area [m²/ft²]	Classification	Max temp
42026	Fine filter, DC 3700c	Pleated around support cylinder	Cellulose, epoxy-treated	1.8 /19.4	IEC EN 60335-2-69 Part 1	176°F/80°C
42026ST	Fine filter x 24	See above	Cellulose	1.8 /19.4	IEC EN 60335-2-69 Part 1	176°F/80°C
42025	Fine filter, DC Wood Shavings Extr.	Pleated	Polyester	1.8 /19.4	IEC EN 60335-2-69 Part 1	176°F/80°C
42025ST	Fine filter x 24	Pleated	Polyester	1.8 /19.4	IEC EN 60335-2-69 Part 1	176°F/80°C
42465	Fine filter, PTFE	Pleated around support cylinder	Polyester, PTFE	1.8 /19.4	IEC EN 60335-2-69 Part 1	176°F/80°C
42024	HEPA filter, DC Wood Shavings Extr., DC 3700c	Pleated	Cellulose, fibreglass	1.5 /16.2	HEPA H13 EN 1822-1	176°F/80°C
4202501	Fine filter	Pleated	Antistatic	1.5 /16.2	IEC EN 60335-2-69 Part 1	176°F/80°C
42398	Fine filter, grounded	Pleated around support cylinder	Polyester	1.8 /19.4	IEC EN 60335-2-69 Part 1	176°F/80°C

Packaging

Dustcontrol Premium Packaging

Dustcontrol is now offering a more robust premium alternative of packaging to protect and secure the transport of larger mobile and semi-mobile units. Premium packaging is designed for fast, quiet and ergonomic mounting/disassembly with the aid of sheet metal clips and tape sealing.

Premium Packaging is an option when ordering and the prices are set according to the table above. Up on return an undamaged packaging to Dustcontrol AB, half of the packaging cost will be credited.

Part No	Description
44637	Premium Packaging for DC 11-Module XL
44638	Premium Packaging for DC 5900 / DC Storm
44639	Premium Packaging for DC Storm
44640	Premium Packaging for DC 11-Module









INVISIBLE

THE HAZARDS ARE WHAT YOU CANNOT SEE

Our mission is to highlight the health concerns and consequences of not using the right equipment. We highlight the dangers – those tiny particles that penetrate deep into the lungs, causing lung cancer, asthma and chronic bronchitis, among other things.
To be a leader in this industry you need a core issue. Ours is health – Technology for Healthy Business. We create products that solve the problems associated with unhealthy working environments and that eliminate the hazards the eye cannot see.

Visit **dustcontrol.com** to read more about
how we can help you with what you cannot see.

www.dustcontrol.com

Contact our Customer Service Department in our Head Office in Norsborg or visit our website for our worldwide distributors for further info, support, service or a demonstration.

Head Office
Dustcontrol AB
Box 3088 • Kumla Gårdsväg 14
145 03 Norsborg, Sweden
Telephone: +46(0)8 531 940 00
support@dustcontrol.se
www.dustcontrol.com

Download our catalogues from Dustcontrol.com





Save time – use QR codes

There are QR codes on all our mobile machines. Scan the code and you will be able to see videos on filter cleaning and how to replace filters and plastic bags.

No QR reader in your smartphone? Download it from the App/Android store

How to use our QR codes?
See our video on YouTube
https://www.youtube.com/watch?v=0BSo-cYF-6MU



Which solution will you choose?

As a true professional, you have high requirements for your equipment. Dustcontrol has been involved with dust extraction and material transport for more than 50 years and we supply dust extractors and air cleaners for all types of applications. No matter what you choose, you can be sure of getting truly professional equipment that is built with your work environment and health in mind.

Dustcontrol Worldwide


AT
Dustcontrol Ges.m.b.H.
info@dustcontrol.at
www.dustcontrol.at


AU
All Preparation Equipment
www.allpreparationequipment.com.au


BA
TENZO d.o.o.
info@tenzo.ba
www.tenzo.ba


BENELUX
Dust Solutions BV
www.dustsolutions.nl


CA
Dustcontrol Canada Inc.
info@dustcontrol.ca
www.dustcontrol.ca


CH
Rosset Technik
Maschinen Werkzeuge AG
info@rosset-technik.ch
www.rosset-technik.ch


CL
Ambitec S.A.
informaciones@ambitec.cl
www.ambitec.cl


CN
Suzhou Dustcollect Filtration
Technology Co. Ltd.
wang@dustcollect.cn
www.dustcollect.cn


CZ / SK
IML TRADING s. r. o.
info@dustextraction.sk
www.dustextraction.sk


DE
Dustcontrol GmbH
info@dustcontrol.de
www.dustcontrol.de


DK
CONSTRUCTION:
Erenfred Pedersen A/S
info@ep.dk
www.ep.dk

INDUSTRY:
Dansk Procesventilation ApS
info@dansk-procesventilation.dk
www.dansk-procesventilation.dk


EE
G-Color Baltic OÜ
sales@g-color.ee
www.g-color.ee


ES
Barin, s.a.
info@barin.es
www.barin.es


GB
Dustcontrol UK Ltd.
sales@dustcontrol.co.uk
www.dustcontrol.co.uk


GR
Mavrogiannakis S.A
ektox@enternet.gr
www.ektoxeftis.com.gr


FI
Dustcontrol FIN OY
dc@dustcontrol.fi
www.dustcontrol.fi


FR
CONSTRUCTION:
SMH Equipements
info@abequipements.com
www.smhequipements.com

INDUSTRY:
Dustcontrol AB
info@dustcontrol.fra
www.dustcontrol.fra


HR
Kermek d.o.o.
kruno.nedeljko@kermek.com
www.kermek.com


HU
Vandras Kft
vandras@t-online.hu
www.vandras.hu


IN
Advance Ventilation Pve Ltd.
sales@advanceventilation.com
www.advanceventilation.com


IT
Airum srl
info@airum.com
www.airum.com


KR
ESH Engineering Co.
eshengco@gmail.com
www.eshengco.com


LT
UAB Hidromega
info@hidromega.lt
www.hidromega.lt


LV
SIA Reaktivs
reaktivs@reaktivs.lv
www.reaktivs.lv


MY, ID
Städa Envirospace Bhd
info@stada.com.my
www.stada.com.my


NO
Teijo Norge A.S
firmapost@teijo.no
www.teijo.no


NZ
Artizan Diamond Tools
enquiry@artizandiamond.co.nz
www.artizandiamond.co.nz


PE
Efixo
contacto@efixo.pe
www.efixo.pe


PH
Sweden Concrete Machines Inc.
peringe@packoskick.se
www.swedenconcretemachines.ph


PL
Bart Sp. z. o.o.
info@bart-vent.pl
www.bart-vent.pl


PT
Metec-Mecano Técnica, Lda.
geral@metec.pt
www.metec.pt


RO
INDUSTRY:
General Contractor Industry SRL
office@gci-grup.ro
www.gci-grup.ro


RO
CONSTRUCTION:
Concept Revolution SRL
office@pardoseli.ro
www.pardoseli.ro


RS
Enel Alati
eneldoo@eunet.rs
www.eneldoo.rs


SE
Dustcontrol AB
info@dustcontrol.se
www.dustcontrol.com


SG
Städa Envirospace Pte Ltd
Info@stada.com.my
www.stada.com.my


TH
Vast Metal and Machinery Co., Ltd.
vastmetal@vastmm.com
www.vastmm.com


TR
Ventek Mühendislik Ltd.
info@ventek.com.tr
www.ventek.com.tr


AE
Global Enterprises Trading Co L.L.C.
sales@globalentco.com
www.globalentco.com

GEM
Industrial Equipment Trading Co.
Tel: +971 4 8840 474
Email: gemuae@eim.ae


UA
MBK Obshemashkontrakt, JSC
zao@omk.dp.ua
www.omk.dp.ua

US
Dustcontrol Inc.
info@dustcontrolusa.com
www.dustcontrol.us

VN
Tayhostar JSC
tayhostar@tayhostar.vn
www.tayhostar.vn

Dustcontrol®

Please contact the head office in Sweden if you do not find a distributor in your area.

info@dustcontrol.se

Strategy and Certifications at Dustcontrol

As part of our ongoing sustainability work, we compile and submit relevant documentation to the web-based platform Ecovadis. Each year, we upload updated materials from our management system, which are then reviewed and assessed by sustainability experts. Based on this evaluation, we receive a score that reflects our performance in areas such as environment, labor & human rights, ethics, and sustainable procurement.

For more information, please visit our website.

COMMITTED
ecovadis
Sustainability Rating
JUN 2026

The four focus areas of Dustcontrols strategy are:




RESPONSIBLE SOURCING
REDUCED ENVIRONMENTAL IMPACT

SUSTAINABLE PRODUCT DEVELOPMENT
ATTRACTIVE WORKPLACE




Dustcontrol is certified in accordance with ISO 9001, 14001 and 45001 with an integrated quality and environmental management system. This includes process management, identifying our environmental footprint, adhering to regulations, and training our employees in the topic. We carefully adhere to the EU's Reach and RoHS directives in order to minimise our use of chemicals. With the help of Lean production, we continuously evaluate our processes and look to improve our overall efficiency.

CERTIFIED ISO 14001 SVENSK CERTIFIERING
CERTIFIED ISO 9001 SVENSK CERTIFIERING
CERTIFIED ISO 45001 SVENSK CERTIFIERING



Dustcontrol QR Codes



Easily scanned using a smartphone, QR codes work like quick links, taking you straight to the information you need. We aim to make it easy for you to find information about our products, such as how to replace and clean the filter, or replace the bag. Our QR codes make it easy to find helpful instructional videos in the language of your choice, including English, Swedish, German or Finnish.

To scan the codes, you will need to download a QR code reader app. These can be obtained free of charge via the App Store, Android Market or similar platforms.

QR codes on our machines & accessories

DC 1800,
DC 2800, DC 2900

DC Tromb

DC 5800, DC 5900,
DC Storm, DC Tromb Turbo

DC AirCube
500 / 1200 / 2000

DC Wet-Vac
50W / 75W

DC Accessories
Food Industry

Go to YouTube for a short guidance:
https://youtu.be/0BSocYF-6MU

Meet our Certified Service Team!

The Dustdoctors at your Service!

We offer a complete service for any of your mobile machines or stationary vacuum systems. If you have a problem with your machine, always contact customer service. In order to get a registration number for your complaint.

Go to www.dustcontrol.com to learn more!

Look out for these Dustdoctors!






Dustcontrol
DC 5900
Dustcontrol
AirCube
Dustcontrol
AirCube



Healthy Business

Dustcontrol®

www.dustcontrol.com

Published by Dustcontrol AB 2026 © www.dustcontrol.com. 20261029. Prod No 903012.